

The Smart Pet Feeder: Progress Report 1

*A Progress Report on the Design and Building of an Automated Pet Feeder Capable of Preventing One Pet  
From Eating Another Pet's Food*

Submitted to Professor Salah Badjou

on March 5, 2008

by

Rachel Heil	Kristine McCarthy	Filip Rege	Alexis Rodriguez-Carlson
802-338-0165	508-280-2562	617-230-0196	617-359-9019
heilr@wit.edu	mccarthyk8@wit.edu	regef@wit.edu	rodriguezcarls@wit.edu
68 Louis Prang St.	610 Huntington Ave.	8 Barton St.	143 Watertown St. #2
Boston, MA 02115	Box 1079	Somerville, MA 02144	Watertown, MA 02472
	Boston, MA 02115		

WENTWORTH INSTITUTE OF TECHNOLOGY

ELMC 461-ELECTROMECHANICAL Design

## Table of Contents:

Introduction:.....	3
Progress-to-date: .....	3
The Control System: .....	3
The Pet Sensing System:.....	3
The Processing System: .....	3
The Time Keeping System: .....	3
The Display System: .....	3
The IDE:.....	3
The Program: .....	3
Program Algorithms: .....	3
The Motor System: .....	3
The Feeder Enclosure: .....	3
Problem Areas:.....	3
Plans for the Next Reporting Period: .....	3
Schedule Status: .....	3
Project References: .....	3
Appendices:.....	3
Appendix A: Microcontroller Datasheet.....	3
Appendix B: Motor Driver Datasheet.....	3
Appendix C: RFID Datasheet .....	3
Appendix D: Real Time Clock Chip Datasheet.....	3
Appendix E: Motor Datasheet .....	3
Appendix F: 24V Power Supply Datasheet .....	3

## **Introduction:**

(Project manager: Alexis Rodriguez-Carlson)

We are currently in the process of designing and building a prototype of the Smart Pet Feeder, an automated pet feeder which will be suitable for use by cats and small dogs. The Smart Pet Feeder will solve two problems which pet owners face, they are:


1. Making sure that each pet has access to a healthy amount of food throughout the day, regardless of the owner's schedule
2. Making sure that each pet eats only its own food

Though there are a variety of products on the market which solve the first problem, there are none which address the second. The Smart Pet Feeder will give pet owners a solution to both problems, thereby improving the lives of both pets and owners by allowing the owner to:

1. Reliably provide food to a pet at the time the owner wishes
2. Keep the pet from reaching the food stored for later feedings
3. Restrict an unauthorized pet access to the feeder


The Smart Pet Feeder will look like the model in Figure 1. It will consist of a tray which holds 6 cups of food and will be mounted to a motor. The motor and the base will be inside an enclosure that will display only one bowl of food at a time. At predetermined times (which are programmable by the owner) the tray will rotate and reveal a fresh cup of food.

The Smart Pet Feeder is designed to feed only one pet. To make sure that no "forbidden pet" eats the food in this feeder there will be a radio frequency identification (RFID) reader mounted to the enclosure of the feeder in front of the revealed bowl (see Figure 1). This reader will be paired with a tag on the forbidden pet's collar. When the reader receives the signal from the tag it will trigger the motor to rotate so that the spot on the tray with no bowl is exposed, thus keeping the forbidden pet from eating.



**Figure 1:** Model of the Smart Pet Feeder

The Smart Pet Feeder consists of three main systems: the Control System, the Motor System, and the Feeder Enclosure (see Figure 2). Each system has a role or roles which it must fulfill. The Control System's purpose is to rotate the tray to a new dish at a programmable time, to rotate the tray to the blank spot if the forbidden pet approaches the feeder, to keep and display an accurate real-time clock, and to allow the owner to easily set both the current time and the time the feeder will rotate to reveal fresh food. The Motor System has to be capable of receiving commands from the microcontroller and then rotating the fully loaded tray an exact distance, and it also must not let the full weight of the tray sit on the shaft of the motor. The Feeder Enclosure must be heavy enough so that a pet cannot turn it over. It must close securely enough that the pet cannot open it and access the food. It must be opened easily so that the owner can refill the dishes, and must protect the electronics inside of it. Also, all of the parts of the feeder that touch food must be washable. A block diagram showing all of the systems and how they interact with one another is in Figure 2.




**Figure 2:** System Block Diagram

## Progress-to-date:

Because the systems that make up the Smart Pet Feeder are so distinct, it is easiest to discuss them one at a time. This section will give a detailed description of each system and how that system helps to fulfill the requirements for the Smart Pet Feeder described above. It will start with the Control System, progress to the Motor System, and end with the Feeder Enclosure.

### The Control System:

The Control System consists of several subsystems: the Pet Sensing System, the Processing System, the Time Keeping System, the Display System, and the Motor Driving System (this subsystem is also part of the Motor System and will be discussed later). This section will detail the requirements for each subsystem in Figure 3, the criteria used to select components, and describe the component that was ultimately chosen to be used.



**Figure 3:** The Control System

## The Pet Sensing System:

(Primarily responsible team members: Kristine McCarthy, Alexis Rodriguez-Carlson)

The Pet Sensing System fulfills the design objective to create a product that can distinguish between different animals in order to not allow the forbidden pet to eat from the feeder. In order to do this it is necessary for the forbidden pet to wear an emitter on its collar that a sensor on the feeder can detect and then react to.

Our requirements for the emitter/sensor pair are:

1. That the emitter be small enough to be worn comfortably on the pet's collar
2. That the emitter does not pose any health risks to the pet
3. That the sensor fit on the feeder
4. That the sensor be able to interface with the microcontroller
5. That the sensor be able to react to the emitter while the pet is still 4-6 inches away from the feeder

The first type of emitter/sensor system that we considered was an infrared emitter paired with a photo transistor since it appeared to satisfy all of our requirements. We knew that the emitter could be mounted on a pet's collar, because this type of technology is already being used in products such as the Staywell Infrared Cat Door (see Figure 4) (this cat door will only open to a cat wearing the correct infrared collar key). It offers no health risks to the pet. Also, infrared sensors come in extremely small sizes, so it could be mounted easily on the feeder and could be interfaced with the microcontroller via a signal conditioning circuit to convert the analog output voltage to an on/off signal. The only condition that we were not sure it fulfilled was the distance the sensor could be from the emitter before it reacted, tests were necessary to determine this.



**Figure 4:** The Staywell Infra-Red Cat Door and the Infra-Red Collar Key [1]

To avoid the time and expense of designing an emitter system, we decided to use a Staywell Collar Key (see Figure 5). This is a small enclosure which holds two batteries and a circuit board with an infrared LED mounted on it.




**Figure 5:** The Staywell Infra-Red Collar Key [2]

After doing some research on infrared sensors, we decided to use a phototransistor. A phototransistor reacts to changes in light with a change in the voltage output from the emitter. Since phototransistors are relatively inexpensive, we ordered four different models to test with the collar key. Their average cost being about \$0.36 apiece.

The phototransistors we ordered were the Sharp PT501, the Sharp PT481, the Sharp PT4800F, and the Fairchild QSC112. All of these phototransistors have only two leads, the collector and the emitter. With the help of Joseph Diecidue, we tested them by connecting a 5V power supply to the collector and either a 100  $\Omega$  or 1 k $\Omega$  resistor between the emitter and ground. Then, we measured the output voltage across that resistor (see



Figure 6). The collar key was held a varying distances from the phototransistor and the phototransistor's reaction was noted.



**Figure 6:** Phototransistor Test Circuit

The results were less than ideal. As seen in Table 1, the voltage change due to the presence of infrared light was a maximum of 75.31 mV. These readings were achieved only by holding the emitter less than 2 inches from the phototransistor, which was much shorter than the required sensing distance for the Smart Pet Feeder. In addition, all of the phototransistors reacted more strongly to changes in ambient light than they did to the emitter, even those which claimed to be unreactive to light in the visible spectrum.

$$R_L = 100\Omega$$

$$R_L = 1k\Omega$$

**PT481**

IR	$V_{OUT}$ (mV)
OFF	0.00
ON	2.22

IR	$V_{OUT}$ (mV)
OFF	0.00
ON	10.03

**PT501**

IR	$V_{OUT}$ (mV)
OFF	0.05
ON	69.32

IR	$V_{OUT}$ (mV)
OFF	0.49
ON	71.42

**PT4800FB**

IR	$V_{OUT}$ (mV)
OFF	0.00
ON	8.31

IR	$V_{OUT}$ (mV)
OFF	0.00
ON	8.31

**QSC112**

IR	$V_{OUT}$ (mV)
OFF	0.04
ON	75.31

IR	$V_{OUT}$ (mV)
OFF	0.55
ON	81.02

**Table 1:** Test results for the phototransistors

We searched for phototransistors whose ranges were longer and found that infrared sensors of a small enough size to use in our product are simply not made to sense a source more than a few inches away. While clearly a similar system can be made to work, as it does work for the Staywell Infra-Red Cat Door, we were not confident that we could create a working system within the time left to complete this project. We then started looking for a different solution.

After researching other sensors, we have chosen to use an RFID tag/reader combination in order to fulfill the main design objective of the Pet Sensing System, which is to detect and react to the approach of the forbidden pet. After looking into a few different companies, we decided to use a Parallax tag/reader combination for a few different reasons. The transponder tags come in very small sizes so a tag can easily be placed on a pet's collar, the sensor is small enough to be mounted to the feeder and can be easily interfaced with the microcontroller (it is a logic device), and we know they have a read range of at least 2 to 4 inches [3]. Also, we have spoken with the manufacturer and know that if we mount the reader behind the cover, which is going to be made out of some sort of acrylic or plexi-glass, it will still function properly. Finally, we have used products from Parallax in the past and were pleased with their quality and performance.

Radio frequency identification (RFID) chips are being used in an increasing number of every day applications. These applications include postage (shipping labels), pet identification via implants (tracking devices), and key cards (school ID cards) [3]. All of these are examples of passive RFID tags or transponders. A passive tag is one that does not have an internal power source and is only operational when a reader is near by and trying to access it. The signal the reader sends is just enough to power the chip long enough to send a signal. This allows them to be used in situations where it is not practical to have a power source or where it is undesirable to have constant radio transmissions. These tags are only useful in applications where short reading distances will be used since they only have a read distance of about 2 to 4 inches [3][4].

Another type of RFID tag is an active tag. Active tags have an internal battery and are constantly looking for the reader signal and sending its own signal to the reader. These tags are generally more reliable than passive tags, because they are able to initialize the session with the reader, generate stronger signals, and

have longer read distances, some of which some are up to 1500 ft. They also tend to be larger in size since they have the onboard power source [3].

One aspect that had to be researched carefully before considering an active tag for the Smart Pet Feeder was the potential for health risks in the pet wearing the active tag. Some studies have shown that RFID chips embedded in lab rats and mice may have caused tumors to form near the site of the chip [5]. However, after doing research on the subject, we found several factors which make us comfortable placing an active tag on the collar of a pet. For example, thousands of tags have been implanted in humans and thus far, no cases have been reported where a tumor has formed [6]. Additionally, Dr. George Demetri, director of the Center for Sarcoma and Bone Oncology at the Dana-Farber Cancer Institute in Boston, said that the incidences of tumors in the rats were reasonably small [5]. This view is further supported by Dr. Cheryl London, who is a veterinary oncologist at Ohio State University, who noted: "It's much easier to cause cancer in mice than it is in people. So it may be that what you're seeing in mice represents an exaggerated phenomenon of what may occur in people [5]." It is also important to note that all the incidents where cancer was said to be caused by RFID tags have occurred when the tag was implanted in the animal.


We are also confident that this technology is safe to use in our application, as it has been approved by the FDA for implantation in humans. There are already proposed plans of placing RFID chips under the skin of humans in order to store medical information. These chips would act like a medical alert bracelets worn today [6][7]. There is one company, Applied Digital Solutions, which has received the FDA approval for this procedure [7].

As we are not planning to implant the tag in the animal, and since there are already products which use RFID technology (such as the PetSage Electronic SmartDoor Pet Door [8]) and we have found no sources which link these products to any health risks for the pet, we feel at this time that it would not pose a risk to the pet's health to use an active tag should it be necessary, but that we will continue to follow the research for new developments.


It is possible that the health risks associated with active tags will not be a concern to us, however, because it is not clear at this time whether an active or a passive tag will work best for our application. At least one of each type being considered has been purchased and testing will be done in order to determine which one is the proper type to use. We would prefer to use the passive tag because of the size difference, the lack of battery, and the lesser amount of radio signals present, but if the passive tag does not serve our purposes, we are comfortable using the active tag.

There were a few non-health related problems with the RFID tags and reader that we had to consider before purchasing them. The first is that they are considerably more expensive than the IR system we originally looked at. The passive RFID tags cost \$2.75, but the active tag was about \$7.00, and the reader was almost \$40.00. This is more than we had originally budgeted for the sensors but could be take from the contingency fund.

The other problem with the RFID chips was size. The passive tags range anywhere from a round 25mm sticker to a credit card sized tag [3]. The sticker is not a problem since it is about the size of an ID tag on a cat's collar, as seen in Figure 7, but the credit card sized tag is simply much too large, as pictured in Figure 8.




**Figure 7:** Passive RFID sticker [3]




**Figure 8:** Passive RFID tag (credit card sized) [3]

The active tag we have ordered is the size of a thin key fob and is pictured in Figure 9.



**Figure 9:** Active RFID Fob [3]

Additionally, the reader is much larger in size than the IR phototransistor. It is about 2.5 in x 3.25 in. as seen in Figure 10. This may be cumbersome, but we believe that we have come up with a solution to the size issue, which will be discussed in the Feeder Enclosure section.



**Figure 10:** RFID Reader Module [3]

The integration of this technology into our project is simple. The reader module will be mounted on the feeder body and the tag on the collar of the forbidden pet. If the forbidden pet approaches the feeder, the reader will receive a signal from the tag and send a message to the microcontroller, which will trigger the motor to rotate the tray to the empty spot, thereby not allowing the forbidden pet to eat. The pet that is supposed to eat from the feeder will not wear a tag and will therefore be allowed to eat from the feeder as long as there is still food available.

In review, the criteria for the Pet Sensing system were that the emitter be small enough to be worn comfortably on the pet's collar, that the emitter not pose any health risks to the pet, that the sensor fit on the feeder, that the system be able to interface with the microcontroller, and that the reader be able to react to the emitter while the pet is still 4-6 inches away from the feeder. We are confident that this technology will allow us to effectively fulfill all of the criteria above. The tag will not cause the forbidden pet discomfort since it is

not bulky, we are now confident that it will not present any health risks to the pet. The reader can be mounted to the body of the feeder and while easily interfacing with the microcontroller. The system will allow the Smart Pet Feeder to recognize the approach of the forbidden pet and to react accordingly while the forbidden pet is still several inches away from the feeder.


#### The Processing System:

(Primarily responsible team member: Alexis Rodriguez-Carlson)

The Processing System is responsible for the integration and control of the Control System and the Motor System, as well as the different subsystems that make up the Control System. It consists of two parts: a microcontroller and the program. The requirements for a microcontroller are:

1. It must be capable of interfacing with all of the other components that make up the Smart Pet Feeder
2. It must have enough memory to hold the programming required to control all of the components
3. It must have enough RAM to run the program
4. It must be affordable


With these requirements in mind, we have chosen to use the Axiom CML12S-DP512 Development Board, which uses the Motorola MC9S1DP512 microprocessor (see Figure 11).



**Figure 11:** The Axiom CML12S-DP512 Development Board

The CML12S was chosen largely due to its affordability, since one of the team members already owned one. It exceeds all of the other requirements, as it has up to 91 in/out ports available to interface with outside equipment, 4 kB of EEPROM and 512 kB of Flash EEPROM to store the program, and 14 kB of SRAM available [9][10]. In future versions of this product a less powerful, less expensive microcontroller would be used, but for now the CML12S will give us ample resources for programming and interfacing without worrying about running out of ports or memory. The electrical and control schematic, which details how all of the components will be connected to the CML12S is in Figure 12.





**Figure 12:** Electrical and Control Schematic

## The Time Keeping System:

(Primarily responsible team member: Kristine McCarthy)

One of the subsystems of the Control System is the Time Keeping system. This is the portion of the design that will keep time, allow the user to program when the feeder should rotate in order to reveal a fresh bowl of food, as well as provide incremental timing. The criteria that this system must meet are:

1. To allow the user to set the time on the clock
2. To tell the feeder to rotate at specific times during the day to reveal fresh food
3. Use a toggle switch as a manual override to prevent the bowls from rotating
4. Allow the user to set the location of the bowls after the time is set
5. When the toggle switch is turned off, allow the program to rotate the bowl to the proper location and also power the RFID module back on to begin searching for the tag
6. Provide incremental timing

To fulfill these requirements, we chose to use three main parts: buttons, a switch, and the real time clock chip (RTC chip). Each of these three components will serve their own function for programming and time keeping while working together.

First, there are the buttons. These are to be used much like the buttons on an alarm clock. Their main function will be to set the time into the RTC as well as to program when the feeder will rotate to reveal fresh food. It eliminates the need for the user to have a computer that is capable of interfacing with the microcontroller and it also means that they do not need the IDE or the knowledge of a programming language to set it. One of the buttons is pictured in Figure 13.



**Figure 13:** Programming Button (photograph by Kristine McCarthy)

Next, there is the switch. The switch is a normal toggle switch that you see every day in many applications. As pictured in Figure 14, it is in the on position. We have decided to incorporate the switch so the user can suspend the feeder's operation. This will allow the user to refill the dishes without the worry of the feeder beginning to turn. This could happen if the user were filling the feeder at the time it is set to rotate, or if the forbidden pet approached the feeder while the owner is filling the dishes, causing the reader to pick up the signal and subsequently turn back to an empty spot. With this system, every subprogram in our main program will first check to see if the switch is in the on or off position. For example, if the switch is off, all programs and subprograms will execute normally. Please see the program section for further detail on this operation.



**Figure 14:** On/Off Toggle Switch [12]

The heart of the Time Keeping System is the real time clock (RTC) chip. An RTC is a chip that stores data for projects that utilize real time applications. It allows the programmer to store time of day data as well as alarm data to be used at a specific time. The DS1286 Watchdog Timekeeper from Dallas Semiconductor, pictured in Figure 15, is an RTC chip that is capable of keeping track of time to the hundredth of a second and is accurate to  $\pm 1$  minute per month. It comes in a 28 pin encapsulated package and has an embedded lithium

power source that maintains the data on the chip in the event of power loss as well as a quartz crystal for timing. The chip is so intelligent that after being set, it knows the date, year, month, knows if the month has less than 31 days, and compensates for leap years [14].

The reason we chose to use this chip in our design is that it will allow us to output a time on an LCD panel and will also allow the user to program what time the “alarms” will go off. In this case, the alarms will be a signal sent from the chip at the user-programmed time in order to tell the microcontroller that it is time to turn the stepper motor to reveal a fresh meal. It is also useful in that it allows the user the freedom of moving the unit without having to reset the time and alarms. Since the chip has a battery backup, all of the data, times, and programming will be stored in the chip if the system loses power even though the LCD panel will not display it [14].



**Figure 15:** DS1286 Watchdog Timekeeper [13]

The chip has two different types of alarms. There is the Watchdog Alarm and the Time of Day alarm. The time of day alarm is just like a regular alarm and the RTC outputs a signal when the preprogrammed time is reached. This function will be used to tell the microcontroller that it is time to turn the stepper motor to reveal a new dish. The Watchdog Alarm functions as a counter. A time is set into the correct register on the chip and that amount of time is counted down to zero [14]. This is the function that will be used to delay the pet detection program after the tag on the forbidden pet has been detected and the bowl has rotated. For example, if the forbidden pet approaches the bowl, the reader on the bowl will detect the tag worn on the collar of the pet and it will send a signal to the microcontroller and cause the bowl to rotate. Once this has happened, the Watchdog timer will begin a 30-second countdown in order to allow the pet time to walk away before the reader tries to sense the collar again. Once the countdown reaches zero, the program will check the reader to see if the tag is sending a signal again.

In summary, the functions of the timing system will be to allow the user to easily set the clock, to program a desired time to reveal a fresh bowl of food, allow the user to decide the positioning of the tray after the time of day is set, allow the feeder to run the main and subprograms when the override is not initiated, and to provide incremental timing. The chip, buttons, and switch allow us to accomplish all of this easily and effectively by allowing ease of use and a wide range of possibilities as the chip can be programmed to feed the pet at any time the user desires.

### The Display System:

(Primarily responsible team member: Rachel Heil)

The display system consists of an liquid crystal display (LCD) panel which will display the time, options for setting the feeder to a specific bowl, and the time at which it should rotate.

The requirements for the LCD panel are as follows:

1. That it is cost effective
2. That it is compatible with the CML12S microcontroller
3. That it be capable of displaying the time and text necessary for the user to program the feeder



**Figure 16:** The LCD panel and its connector

The display chosen is a generic LCD panel. This panel was chosen because it is expressly manufactured to work with the CML12S. The selected LCD panel is shown in Figure 16. Exact details and data on the

display are unavailable and the specific details on exactly how it is going to work with the CML12S are still being determined. However, we do know it easily connects to the microcontroller through the LCD port on the CML12S. Another reason the LCD panel was chosen is that it is affordable at a price of \$35. This panel will be able to display four lines of text that are twenty characters long. This should provide ample amount of space to display the time and setting options necessary. A short program will be created to control what the LCD panel displays.

### The IDE:

(Primarily responsible team member: Rachel Heil)

The Integrated Development Environment (IDE) is the software in which we will write and compile the code that will control the microcontroller. The requirements for the IDE are as follows:

1. That it is cost effective
2. That it allows each team member to have a copy of the software in order for each team member to program simultaneously
3. That it be compatible with the HC12 microcontroller
4. That it allow us to program using the C language
5. That it be easy to use

The IDE that has been chosen is Embedded GNU. This software fully meets all of our requirements. It is an open source software package, which means that it is completely free with no expiring trial period. This is ideal, as we are working on a budget and will be using the software longer than the typical 45-day trial period. This also allows us to each have the software on our computers, thus allowing simultaneous programming.

Other programs that were looked into were Image Craft, miniIDE, AxIDE, and CodeWarrior. Each of these had their own conflicts. The conflict encountered with the Image Craft software was that it had a trial period of 45 days that would make it more difficult for us to program simultaneously. When trying to use CodeWarrior, a nice program which was available to us free of cost, a communication issue arose which

wouldn't allow the board to talk to the computer. The only issue with the miniIDE and AxIDE programs was that they did not allow for C programming, which was an essential requirement for choosing an IDE.


Another main reason that the Embedded GNU software was chosen is that it allows us to do the programming for our project in the C language. The advantage to using an IDE that allows us to program in C is that we are already familiar with the C language. Since we are all familiar with C, this seemed to be the logical language to use. This allows us to spread out the programming workload so that no one person is responsible for all programming and it can be done in a more reasonable period of time. Programming in C is crucial so that we are not wasting time trying to learn how to program in an unfamiliar language or the more tedious and time consuming Assembly language.

The software has been tested with the CML12S and allows communication, memory modification, and programming. The interface is fairly simple and easy to use. It is similar to programs in which the team members have used previously in order to program using the HC11 microcontrollers.

#### The Program:

(Primarily responsible team member: Alexis Rodriguez-Carlson)

The program is still very much in the planning stage. At this point, it is thought that it will consist of a main program and at least 4 sub-programs.



**Figure 17:** Block diagram of the program

The criteria for the program are that it:

1. Control the microcontroller and all of the components (Main Program)
2. Provide a means for the user to set the time (Clockset Program)

3. Provide a means for the user to program the time that the motor will rotate to reveal fresh food (Clockset Program)
4. Provide a way for the user to suspend operation while refilling the food dishes (Clockset Program)
5. Keep track of which dish is revealed so that the system knows how far it must rotate to reveal the blank spot (Feeding Time Program)
6. Monitor the RTC chip to see if it is sending an alarm signal (Feeding Time Program)
7. Monitor the RFID reader to see if it is receiving a signal from the tag (Pet Detect Program)


At this time, a rough algorithm for the Main program, the Feeding Time, and the Pet Detect Program have been created and can be seen in the following section.

#### Program Algorithms:

(Primarily responsible team member: Alexis Rodriguez-Carlson)

Definition of variables:

BOWL – an integer variable which represents the location on the tray revealed by the feeder according to Figure 18 below. The blue circle represents the location currently revealed by the feeder, and the circle labeled 0 is the blank spot.



**Figure 18:** A not-to-scale representation of the pet feeder tray


SLICE – A floating number variable which represents the distance the motor must rotate in order to advance the tray to the next numbered location

Main Program:

1. Check to see if the override switch is on



- a. If the switch is on, call the Clockset subprogram
- b. If the switch is off, call the Pet Detect subprogram




**Figure 19:** Flowchart of Main Program

Pet Detect Program:

1. Check to see if the override switch is on
  - a. If the switch is on, call the Clockset subprogram
  - b. If the switch is off, check to see if the RFID Reader is receiving a signal from the tag
    - i. If it is not, call the Feeding Time Program
    - ii. If it is, trigger the motor to rotate the tray counter clockwise a distance of BOWL x SLICE
    - iii. After rotation, wait 30 seconds (using the timer feature of the RTC), then check to see if the RFID Reader is receiving a signal
      1. If it is, go back to Line 1.b.iii
      2. If it is not, trigger the motor to rotate the tray clockwise a distance of BOWL x SLICE
      3. Call the Feeding Time subprogram

#### Pet Detect Subprogram




**Figure 20:** Flowchart for Pet Detect subprogram

#### Feeding Time Program:

1. Check to see if the override switch is on
  - a. If the switch is on, call the Clockset subprogram

- b. If the switch is off, check to see if the RTC is sending an alarm signal
  - i. If the RTC is not sending a signal, call the Pet Detect subprogram
  - ii. If the RTC is sending a signal, increment the variable BOWL by 1
  - iii. After incrementing, check to see if the RFID Reader is receiving a signal from the tag
    - 1. If the RFID Reader is not receiving a signal from the tag, trigger the motor to rotate the tray clockwise a distance of SLICE
    - 2. If the RFID Reader is receiving a signal from the tag, trigger the motor to rotate the tray counter clockwise a distance of  $(BOWL-1) \times SLICE$ 
      - a. After rotation, wait 30 seconds (using the timer feature of the RTC), then check to see if the RFID Reader is receiving a signal from the tag
        - i. If the RFID Reader is receiving a signal, go back to Line 1.b.iii.2.a
        - ii. If RFID Reader is not receiving a signal, trigger the motor to rotate the tray clockwise a distance of  $BOWL \times SLICE$
  - iv. Check to see if BOWL is equal to 7
    - 1. If BOWL is equal to 7, set BOWL equal to 0
      - a. Then, call the Pet Detect subprogram
    - 2. If BOWL is not equal to 7, call the Pet Detect subprogram



**Figure 21:** Flowchart of Feeding Time subprogram

### The Motor System:

(Primarily responsible team member: Filip Rege)

As Figure 22 shows, the motor system consists of the following components: stepping motor, motor driver, power supply and tray support.




Figure 22: Block Diagram of the Motor System

The stepping motor provides rotational motion for the tray with the bowls whenever it receives a command to do so from the microcontroller. There are two scenarios when this happens. The first one is the user programmed feeding time and the second one is the proximity of the forbidden pet.

The reason why we selected a stepping motor over another type of motor is its ability to rotate in precise steps as opposed to spinning continuously, like a DC motor for example, and it does not require position feedback like a servo motor.

The motor to be selected for the Smart Pet Feeder has to:

- To be able to be controlled by the CML12S
- Be able to rotate the fully loaded food tray (including pet food) to a precise location
- Not be more expensive than \$50.00

After choosing to use a stepping motor the following questions need to be answered. Should the motor be unipolar or bipolar? What does the output torque need to be so the motor can operate at the desired speed and with the right acceleration? How fine should the step size be?

The difference between a unipolar and a bipolar motor is the complexity of their internal coils winding. The bipolar motor is much simpler in terms of its internal construction, has a higher torque-to-size ratio than a unipolar motor but requires a much more complex external circuitry to control it. A unipolar motor, on the other hand, is more complex in terms of its internal arrangements, has less torque than a bipolar motor of the same size, is more expensive but also is much easier to control. Because our design team worked with unipolar motors in the past, it was our first choice for the automated pet feeder.

Traditionally, a number of mathematical equations would be used to calculate the needed output torque and the motor's power consumption. However, there is an easier way. Lin Engineering, a California-based company that specializes in motor design and manufacture, offers an easy-to-use tool for a stepping motor selection on their website. Figure 23 and Figure 24 are screenshots showing the use of this tool. The shape and size of the load are entered in the appropriate fields as well as the maximum desired speed and acceleration in addition to the available power specifications. For this project, the weight of the load was determined using SolidWorks. The necessary maximum speed of the motor and the time to reach this speed were estimated at 1 RPS (Revolution Per Second) and 0.5 second, respectively. These values resulted mainly from customer complaints about similar products that are currently at the market. These state that the speed at which the cover rotates is too slow, which allows the pet to eat while the feeder is in motion.

The next choice to be made is the size of the step. A stepping motor is designed to revolve in precise increments, or steps, in addition to continuous rotation. One step is typically the smallest distance the motor can turn, although some motors allow for micro stepping as well. The step size depends on the motor but  $1.8^\circ$  step and  $0.9^\circ$  step are the most common. Generally, the smaller the step size the more precise the motor's movement.

With the help of the Lin Engineering's online motor selection process we chose to use the 4118M-06 unipolar stepping motor. It has more than enough torque to turn the tray full of pet food at the maximum speed of 1 RPS. Its 1.8° step size guarantees good accuracy when revolving the tray.

**Direct Drive**

Project name **Auto Pet Feeder**

---

**What is the shape of the load?**

☐ Thin Plate

☒ Thin Circular Disk

☐ Cylinder


☐ Slender Rod

☐ Sphere

☐ Thin Ring

☐ Cone

☐ Hemisphere



---

Disk Radius  Inches

---

Top Speed  RPS

Weight of the Load  Lbs

Acceptable time to accelerate to top speed  Seconds

Axis of Rotation: ☐ X ☐ Y ☒ Z

Rotational offset from center of gravity  Inches

Maximum Available Current  Amps

Maximum Available Voltage  Volts (DC)

---

**BACK** **SUBMIT** **RESET**





















































Figure 23: First Step in Motor Selection

Please select a model. For detailed specifications, please click on the motor model or image.

\* Torque values are reported as Holding Torque in units of oz-in ([more](#))

On average dynamic torque is approximately **70%** of holding torque.

The required dynamic torque for your application is 18.75 oz-in

1.8 Degree Motors				0.9 Degree Motors				0.45 Degree Motors			
NEMA 11		Torque*		NEMA 14		Torque*		NEMA 23		Torque*	
		<a href="#">211-13</a>	9.2			<a href="#">3609Z</a>	4.0			<a href="#">5704X</a>	75
		<a href="#">211-18</a>	13.7			<a href="#">3609V</a>	16.0			<a href="#">5704M</a>	140
		<a href="#">211-20</a>	16.6								
NEMA 14		Torque*		NEMA 17		Torque*		Motors shaded out do not meet your calculated torque requirements. However, they can still be selected. Please consider using a gearbox if applicable.			
		<a href="#">3518X</a>	7.5			<a href="#">417-11</a>	17.5				
						<a href="#">417-13</a>	28.0				
						<a href="#">417-15</a>	32.0				
NEMA 17		Torque*		NEMA 17		Torque*					
		<a href="#">4118S</a>	45.0			<a href="#">4209S</a>	35.2				
		<a href="#">4118M</a>	63.0			<a href="#">4209M</a>	55.44				
		<a href="#">4118L</a>	83.0			<a href="#">4209L</a>	70.0				
NEMA 23		Torque*		NEMA 23		Torque*					
		<a href="#">5718X</a>	100			<a href="#">4109Z</a>	3.0				
		<a href="#">5718M</a>	173			<a href="#">4109Y</a>	6.0				
		<a href="#">5718L</a>	294			<a href="#">4109X</a>	7.0				
					<a href="#">4109V</a>	15.0					
					<a href="#">4109R</a>	22.0					
NEMA 34		Torque*		NEMA 34		Torque*					
		<a href="#">8718S</a>	424			<a href="#">416-05</a>	6.0				
		<a href="#">8718M</a>	851			<a href="#">416-06</a>	7.0				
		<a href="#">8718L</a>	1288			<a href="#">416-07</a>	8.0				
NEMA 23		Torque*		NEMA 23		Torque*					
		<a href="#">5709X</a>	92			<a href="#">5709X</a>	92				
		<a href="#">5709M</a>	170			<a href="#">5709M</a>	170				
		<a href="#">5709L</a>	260			<a href="#">5709L</a>	260				

BACK

NEXT

Figure 24: Second Step in Motor Selection



Frame Size 17  
STEP SIZE 1.8°



**Super Torque Motor - 4118**



- NEMA Size 17 Mounting
- Cost Effective
- Custom Windings Available (No additional cost)
- Inquire about RoHS versions

**BIPOLAR**

Dimension "A"	Model Number	Amp/Phase	Holding Torque oz-in	Holding Torque N-m	Resistance Ohm/Phase	Inductance mH/Phase	Inertia oz-in <sup>2</sup>	Weight Lbs.	Number of Leads
1.34" 34.0 mm	4118S-02	1.30	45.0	0.32	2.8	3.6	0.18	0.40	4
	4118S-04S	0.67	45.0	0.32	9.9	12.5	0.18	0.40	4
	4118S-04P	1.34	45.0	0.32	2.5	3.1	0.18	0.40	4
	4118S-09	0.90	45.0	0.32	5.3	6.7	0.18	0.40	4
1.58" 40.1 mm	4118M-01	1.70	63.0	0.44	1.5	3.0	0.28	0.60	4
	4118M-06S	0.70	63.0	0.44	10.8	21.8	0.28	0.60	4
	4118M-06P	1.40	63.0	0.44	2.7	5.5	0.28	0.60	4
1.89" 48.0 mm	4118L-01	2.00	83.0	0.59	1.4	2.7	0.37	0.70	4
	4118L-07S	1.05	83.0	0.59	5.2	9.4	0.37	0.70	4
	4118L-07P	2.10	83.0	0.59	1.3	2.3	0.37	0.70	4
2.34" 59.9 mm	4118C-01	2.0	125	0.89	2.0	3.3	0.56	0.90	4

**UNIPOLAR**

Dimension "A"	Model Number	Amp/Phase	Holding Torque oz-in	Holding Torque N-m	Resistance Ohm/Phase	Inductance mH/Phase	Inertia oz-in <sup>2</sup>	Weight Lbs.	Number of Leads
1.34" 34.0 mm	4118S-04	0.95	30.0	0.21	5.0	3.1	0.18	0.40	6
1.58" 40.1 mm	4118M-06	1.00	45.0	0.32	5.4	5.5	0.28	0.60	6
1.89" 48.0 mm	4118L-07	1.50	65.0	0.46	2.6	2.3	0.37	0.70	6
	4118L-25	0.45	65.0	0.46	25.0	17.4	0.37	0.70	6

Figure 25: Third Step in Motor Selection

Once the power consumption of a stepping motor is known a power supply can be selected. The following requirements must be considered:

- Compatibility with the motor
- Cost effective (less than \$30.00)

Lin Engineering recommends the PS1-100-24 (Figure 26), a source with 120VAC input and 24V DC output capable of delivering up to 4.5A of current. Since the motor needs only 1.5A at 24V DC this power

source is more than adequate. Because the HC12 can neither deliver nor receive more than 60mA it must be isolated from the motor by a driver chip.



Figure 26: PS1-100W-24 Power Supply

A driver chip is an integrated circuit (IC) that serves two purposes: it controls the flow of the current through the motor and protects the microcontroller from the motor's high current. Different types of drivers exist and one needs to select the appropriate chip depending on the type of motor and its power rating. The driver chip we chose to use had to meet the following criteria:

- It had to be capable of handling the voltage (24V DC) and the current (1.5A) necessary for the motor's operation.
- It had to be easily interfaced with the microcontroller
- It should cost less than \$10.00

The SanKen manufactured SLA7026M (Figure 27) driver chip is a good choice for the 4118M-06 because it meets all the requirements: it is capable of handling up to 5.0A of current and up to 46VDC, which is more than enough considering that the motor draws only 1.5A at 24VDC.



Figure 27: SLA7026M Driver Chip

### The Feeder Enclosure:

(Primarily responsible team members: Filip Rege)

The main function of the feeder enclosure is to provide protection for the electronics inside, and to prevent the pet from accessing the food stored for later feedings. In order to achieve these goals it has to:

- Be strong enough to withstand the weight of the pet
- Be capable of preventing the pet from accessing food stored for later meals
- Provide access to the food at the same location every time
- Be heavy enough to prevent the pet from turning it over
- Have a removable cover so the user can easily access the bowls
- Have easily removable dish-washer safe bowls




Figure 28: Block Diagram of the Feeder Enclosure Subsystem

As Figure 28 and Figure 29 show, the Feeder Enclosure consists of several parts: the base, the body and the lid. Inside the enclosure, there is the food tray with the bowls and the motor system. The base is to be made of dense material in order to keep the feeder's center of gravity low to prevent the pet from turning it over and eating the food stored in it. The body will most likely be made of aluminum and there will be a clear acrylic enclosure on the front panel to house the receiver. The food tray has already been machined from 6061 aluminum alloy. The lid is also going to be clear acrylic so the user can see how much food is left in the feeder. It will be secured to the rest of the enclosure with a thumb screw that will make it both easy to remove and sturdy enough so that the pet will not be able to get to the food inside.




Figure 29: Exploded View of the Feeder Body

We are planning on using a tray support to isolate the weight of the load from the motor's shaft.

Stepping motors are designed to carry torsional loads but not axial loads. In other words, they are not equipped to withstand with loads that either pull or push on the shaft of the motor.

Because this component is still in the developmental stage its final form has not yet been determined. It will, most likely, be a rectangular plate machined from 6061 aluminum alloy with a circular hole in the middle. The motor will be fastened to the bottom of the plate so that its shaft protrudes through the hole. A rotary table (Figure 30) will be mounted in between the top of the plate and the bottom of the food tray. This composition

will allow for the motor's shaft to be physically connected to the food tray but at the same time it will prevent the weight of the tray to rest on the motor's shaft.



Figure 30: Rotary Table

In summary, the 4118M-06 stepping motor will turn the tray with pet food to reveal a fresh serving at user preset times. It will also turn the tray to the empty position (Figure 29) every time the RFID reader registers the proximity of the “forbidden” pet. The motor will be connected to the microcontroller as well as to the PS1-100-24 power supply through the SLA7026M driver chip. The feeder enclosure will prevent the pets from accessing the food stored inside of it either by turning the feeder over or by pulling the lid off. At the same time, it will be easy for the user to remove the lid to clean or refill the food bowls. Additionally, the enclosure will provide protection to the electronic components inside of it. The weight of the tray will be isolated from the motor's shaft by interfacing both with the tray support.

### **Problem Areas:**

We have encountered several problems during this process. Early on, one of our team members had a death in the family and could not be present for the oral proposal. Then, we determined that we could not use an infrared system for the Pet Sensing System. Though we solved that immediate problem by moving to an RFID system, that system is currently on back order and will not arrive until late March. Lastly, the process of choosing and procuring a motor has been rather difficult.

Presenting the proposal without all of the team members present meant that everyone had to do a little more speaking, but the team was well-prepared and the presentation came together very well. This absence also

caused us to fall slightly behind schedule in that we did not have all of the components chosen as early as we had hoped. Nevertheless, with a little extra work we were able to catch up and order the components on the date we planned.

The next issue came from the infrared system. In our initial stages of design, we had chosen to use an infrared emitter/sensor pair for the Pet Sensing System. We purchased an emitter designed to be used on a pet collar (see Figure 5) and ordered several sensors. When testing these sensors, we discovered that the sensors did not have a large enough read distance or angle for our purposes. This was a possibility we were prepared for, but had decided to chance it because the sensors are relatively cheap and the company we ordered them from shipped them very quickly, so it was not a huge loss of time or money.

In order to resolve this problem, we consulted with one of the lab technicians at Wentworth and he recommended using an RFID system instead. After some research we have ordered a Parallax RFID Reader and three tags (two passive and one active). Unfortunately, after ordering these components, we received notification that the receiver was out of stock and that they would not be able to ship the order until March 14 so we will not be able to test these components until late March. This is not an insurmountable problem because we know that the tags will work with this reader since they were manufactured to do so. In the meantime, we can simulate a signal from the RFID Reader to test our program should we need to.

Our final problem was with the stepper motor that we ordered. We had intended to order a unipolar motor, but accidentally order a bipolar motor. The circuitry for a bipolar motor is much more complex and none of us have any experience with the programming for bipolar motors. Also, the driver chips which we bought to control the motor will not work with a bipolar motor. This problem was resolved by calling the company and arranging to return the motor and then ordering a unipolar motor from another company. This motor should arrive during spring break.

Thus far, we have not encountered any financial problems since we included a contingency fund in our budget. Also, we have been able to get some of the materials for the manufacture of the feeder enclosure free of charge. This has come in very handy since we have run into unexpected expenses associated with changing

sensor types and because we had failed to account for the shipping charges associated with each of the items we have ordered.

### **Plans for the Next Reporting Period:**


For the next few weeks, there are many tasks planned that center around programming and finalization of design. These tasks include preliminary code and flow charts for the Feeding Time and Motor Rotate subprograms, and learning how to use the RTC to keep time, send triggers to the microcontroller, and to measure time increments. Also, we need to become more familiar with the IDE we have chosen to use.

As far as the more physical aspect of our design, there are a few key items that still need to be designed and purchased. First, we need to purchase the material for the base and cover of the feeder and then machine those parts. Next, we need to finalize the design for a system that will keep the weight of the tray off of the shaft of the stepper motor. Once this is designed, parts can be ordered and the system can be built.

Once all of this is completed we will assemble the pieces into a working prototype. Our goal is to have the prototype completed by the middle of April in order to have time before the final presentation to test the system, including trials with real animals, and to debug and troubleshoot any problems which may arise.

For details, please see the Gantt chart on the following pages, which details the time from March 1, 2008 until April 30, 2008.






**Figure 31:** Gantt Chart for March and April 2008 part 1




**Figure 32:** Gantt Chart for March and April 2008 part 2

**Schedule Status:**


At this time, we are exactly on schedule with two exceptions: we had planned to have all of the major components in hand by March 1, and we will not have the RFID Reader with the tags and the motor until mid March. Please see the Gantt chart on the following pages, which details the time from January 28, 2008 until March 1, 2008.



**Figure 33:** Gantt Chart for January and February 2008 part 1



**Figure 34:** Gantt Chart for January and February 2008 part 2



**Figure 35:** Gantt Chart for January and February 2008 part 2

## **Project References:**

- [1] "Staywell Infra-Red Cat Door." Moorepet-petdoors.Com. 28 Feb. 2008 <<http://www.moorepet-petdoors.com/PhotoGallery.asp?ProductCode=500US>>
- [2] "Staywell Infra-Red Collar Key." Petco.Com. 28 Feb. 2008  
<[http://www.petco.com/shop/product.aspx?sku=968170&cm\\_ven=tag&cm\\_cat=34&cm\\_pla=968170&cm\\_ite=968170](http://www.petco.com/shop/product.aspx?sku=968170&cm_ven=tag&cm_cat=34&cm_pla=968170&cm_ite=968170)>
- [3] "RFID Reader Module (#28140)." Parallax, Inc. Rocklin: 2005.
- [4] "Radio-Frequency Identification." Wikipedia. 2 Mar. 2008. Wikimedia Foundation, Inc. 20 Feb. 2008  
<<http://en.wikipedia.org/wiki/RFID>>.
- [5] Lewan, Todd. "Chip Implants Linked to Animal Tumors." Washingtonpost.Com. 8 Sept. 2007. The Associated Press. 2 Mar. 2008 <[http://www.washingtonpost.com/wp-dyn/content/article/2007/09/08/AR2007090800997\\_pf.html](http://www.washingtonpost.com/wp-dyn/content/article/2007/09/08/AR2007090800997_pf.html)>.
- [6] Cheung, Humphrey. "American Medical Association Wants Implantable RFID Chips." TG Daily. 27 June 2007. Tigervision Media. 28 Feb. 2008 <<http://www.tgdaily.com/content/view/32663/113/>>.
- [7] Greene, Thomas C. "Feds Approve Human RFID Implants." The Register. 14 Oct. 2004. 2 Mar. 2008  
<[http://www.theregister.co.uk/2004/10/14/human\\_rfid\\_implants/](http://www.theregister.co.uk/2004/10/14/human_rfid_implants/)>.
- [8] "PetSafe Electronic SmartDoor Pet Door." PetFrenzy.com. 3 Mar. 2008.
- [9] "CML-9S12DP512." Axman.com. 1 Mar. 2008.
- [10] "CML-9S12DP256." Axiom Manufacturing. Garland: 2004.
- [11] "MC9S12DP512 Device Guide V01.25." Freescale Semiconductor, Inc. Chandler: 2005
- [12] "Full size Toggle Switch." Jameco.com. 03 Mar. 2008. <  
<http://www.jameco.com/webapp/wcs/stores/servlet/ProductDisplay?langId=-1&storeId=10001&catalogId=10001&pa=76232&productId=76232>>

- [13] “DS1286 Watchdog Timekeeper.” Jameco.com. 03 Mar. 2008. <  
http://www.jameco.com/webapp/wcs/stores/servlet/ProductDisplay?langId=-  
1&storeId=10001&catalogId=10001&productId=133444>
- [14] “DS1286 Watchdog Timekeeper.” Dallas Semiconductor.
- [15] “Open drain.” Wikipedia.com. 16 Jan. 2008. 29 Feb. 2008.  
<http://en.wikipedia.org/wiki/Open\_drain>
- [16] “Sharp PT481/PT481F/PT483F1 Narrow Acceptance High Sensitivity Phototransistor.” Sharp Electronics.
- [17] “PT501/PT510 TO-18 Type Narrow Acceptance High Sensitivity Phototransistor.” Sharp Electronics.
- [18] “PT4800/PT4800F/PT4810/PT4810F/PT4850F Thin Type Phototransistor.” Sharp Electronics.
- [19] “QSC112, QSC113, QSC114 Plastic Silicon Infrared Phototransistor.” Fairchild Semiconductor. 2005.
- [20] “The Overweight Pet.” ThePetCenter.Com. 25 Jan. 2008  
<http://www.thepetcenter.com/imtop/overweight.html>.
- [21] “Petmate Café Feeder.” Amazon.com. 25 Jan. 2008  
<http://www.amazon.com/gp/product/B0002DI2XC/ref=s9\_asin\_image\_1?pf\_rd\_m=AT  
VPDKIKX0DER&pf\_rd\_s=center-  
2&pf\_rd\_r=0WDC23RF23M58AJ1CCJG&pf\_rd\_t=101&pf\_rd\_p=278240301&pf\_rd\_i=507846>
- [22] “Petmate Le Bistro Electronic Portion-Control Automatic Pet Feeder.” Amazon.com. 25 Jan. 2008  
<http://www.amazon.com/gp/product/B000BVWVUA/ref=s9\_asin\_image\_2?pf\_rd\_m=ATVPDKIKX0DER&p  
f\_rd\_s=center-  
2&pf\_rd\_r=0WDC23RF23M58AJ1CCJG&pf\_rd\_t=101&pf\_rd\_p=278240301&pf\_rd\_i=507846>.
- [23] “Petmate Le Bistro Electronic Portion-Control Automatic Pet Feeder Customer Reviews.” Amazon.com.  
25 Jan. 2008  
<http://www.amazon.com/review/product/B000BVWVUA/ref=dp\_db\_cm\_cr\_acr\_txt?%5Fencoding=UTF8&s  
howViewpoints=1>.



- [24] “Perfect Petfeeder Lux Model.” Pillar Pet Products, Inc. 25 Jan. 2008  
<<http://www.perfectpetfeeder.com/default.html>>.
- [25] “Pet Product Review: Perfect Petfeeder.” Itchmo: News For Dogs & Cats. 25 Jan. 2008  
<<http://www.itchmo.com/pet-product-review-perfect-petfeeder-3428>>.
- [26] “ERGO 8 Day Feeder.” Pet Street Mall. 25 Jan. 2008 <<http://www.petstreetmall.com/Automatic-8-Day-Feeder/5052/1896/>>.
- [27] “How to Keep Your Dog from Eating Your Cat’s Food.” wikiHow.com. 25 Jan. 2008  
<<http://www.wikihow.com/Keep-Your-Dog-from-Eating-Your-Cat's-Food>>.
- [28] “Industry Statistics & Trends”. American Pet Products Manufacturers Association, Inc. 25 Jan. 2008  
<[http://www.appma.org/press\\_industrytrends.asp](http://www.appma.org/press_industrytrends.asp)>.
- [29] “Do You Like Pets Better Than People?”. CBS News. 25 Jan. 2008  
<<http://www.cbsnews.com/stories/2007/09/05/opinion/garver/main3234187.shtml>>.
- [30] “The Pet Economy”. Business Week. 25 Jan. 2008  
<[http://www.businessweek.com/magazine/content/07\\_32/b4045001.htm](http://www.businessweek.com/magazine/content/07_32/b4045001.htm)>.
- [31] “It’s a Pet Economy”. Sacramento Business Journal. 25 Jan. 2008  
<<http://www.bizjournals.com/sacramento/stories/2007/08/20/story3.html>>.
- [32] “The Overweight Pet”. The Pet Center. 25 Jan. 2008  
<<http://www.thepetcenter.com/imtop/overweight.html>>.
- [33] “Dog Owner’s Guide: Obesity”. CanisMajor.com. 25 Jan. 2008  
<<http://www.canismajor.com/dog/obese.html>>.

**Appendices:**

Appendix A: Microcontroller Datasheet.....	3
Appendix B: Motor Driver Datasheet.....	3
Appendix C: RFID Datasheet .....	3
Appendix D: Real Time Clock Chip Datasheet.....	3
Appendix E: Motor Datasheet .....	3
Appendix F: 24V Power Supply Datasheet .....	3

## Appendix A: Microcontroller Datasheet

# CML12S-DP256

Development Board for Motorola MC9S12DP256

CML12SDP256

01/30/04

## CONTENTS

<b>GETTING STARTED .....</b>	<b>3</b>
Installing the Software .....	4
Board Startup .....	4
Support Software .....	4
Software Development .....	5
<b>TUTORIAL .....</b>	<b>5</b>
Creating Source Code .....	5
Assembling source code .....	8
Running your application .....	7
Programming HCS12 Flash EEPROM .....	8
<b>MON12 OPERATION .....</b>	<b>9</b>
Mon12 Monitor Commands .....	10
MON12 Interrupt Support .....	10
MON12 and NOICE Memory Map .....	11
<b>NOICE OPERATION .....</b>	<b>11</b>
<b>BDM OPERATION .....</b>	<b>12</b>
<b>AUTOSTART .....</b>	<b>12</b>
<b>OPTIONS AND JUMPERS .....</b>	<b>13</b>
MEM_EN .....	13
ECS .....	13
MODC .....	13
AUTO OFF / spare .....	14
MODE .....	14
OSC_SEL .....	14
ROM_OFF .....	14
JP1 and JP2 .....	14
CUT AWAY OPTIONS 1 - 6 .....	15
<b>PORTS AND CONNECTORS .....</b>	<b>15</b>
TB1 and J1 Power .....	15
MCU_PORT .....	16
ANALOG PORT .....	16
BUS_PORT .....	17
KEYPAD / PORT H .....	17
P_COM1 and P_COM2 .....	17
CAN PORT .....	18
P1 - P4 HCS12 Header Ring .....	19
LCD_PORT .....	19
BDM PORT .....	20
TEST POINTS .....	20
<b>TROUBLESHOOTING .....</b>	<b>21</b>
TABLE 1: LCD Command and Character Codes .....	23
TABLE 2: MON12 Service Routine Jump Table .....	24
TABLE 3: MON12 Interrupt Table .....	25

## GETTING STARTED

The Axiom CML12S-DP256 single board computer is a fully assembled, fully functional development system for the Motorola MC9S12DP256 microcontroller. Provided with wall plug power supply and serial cable. Support software for this development board is provided for Windows 95/98/NT/2000/XP operating systems.

This development board applies option selection jumpers. Terminology for application of the option jumpers is as follows:

Jumper on, in, or installed = jumper is a plastic shunt that fits across 2 pins and the shunt is installed so that the 2 pins are connected with the shunt.

Jumper off, out, or idle = jumper or shunt is installed so that only 1 pin holds the shunt, no 2 pins are connected, or jumper is removed. It is recommended that the jumpers be idled by installing on 1 pin so they will not be lost.

Development board users should also be familiar with the hardware and software operation of the target HCS12 device, refer to the Motorola User Guide for the device and the CPU12 Reference Manual for details. The development board purpose is to assist the user in quickly developing an application with a known working environment or to provide an evaluation platform for the target HCS12. Users should be familiar with memory mapping, memory types, and embedded software design for the fastest successful application development.

Application development maybe performed by applying the embedded MON12 (default) or NOICE firmware monitors, or by applying a BDM cable with supporting host software. The MON12 monitor provides an effective debug method for assembly level software, but has limitations in C code developments. For C/C++ code development it is recommended that source code or symbolic debug capability be provided in the debugging environment. The NOICE monitor or BDM interface with supporting software tools should be applied for C/C++ code development so the host PC can provide the symbolic support needed. User should verify the NOICE or BDM development environment supports the C compiler to be applied, not all development environments support all compilers.

The MON12 and NOICE monitors are provided in the development board HCS12 internal flash memory and apply some HCS12 resources for operation. See the respective chapter for each monitor for details on operation and resources applied. User should note both monitors apply operation of the HCS12 expanded wide mode data and address bus on HCS12 I/O ports A, B, E, and K for access to the external Ram. The external ram provides a development memory where code to be debugged can be loaded or modified quickly and software breakpoints applied. After the application is tested, the code can be relocated to the internal flash memory space of the HCS12 and programmed into the flash memory for dedicated operation.

User applications developed by applying MON12 or NOICE monitors can be modified and relocated for operation as a stand-alone application. By applying the MON12 Autostart feature, the user application will operate from Reset or Power on conditions to provide a dedicated operation of the application. See the Autostart section in this manual for more information.

Follow the steps in this section to get started quickly and verify everything is working correctly.

## Installing the Software

1. Insert the Axiom 68HC12 support CD in your PC. If the setup program does not start, run the file called "SETUP.EXE" on the disk.
2. Follow the instructions on screen to install the support software onto your PC. You should at minimum install the AxiDE for Windows software.
3. The programming utility "AxiDE" requires you to specify your board. You should select "CML12SDP256" version of your development board.

## Board Startup

Follow these steps to connect and power on the board for the default Monitor operation. This assumes you're using the provided AxiDE utility (installed in the previous section) or a similar communications terminal program on your PC. If you're using a different terminal program than the one provided, set it's parameters to 9600 baud, N,8,1.

1. Set the CML12Sxxx board Option jumpers to default positions:

**MEM-EN = IN, ECS = IN, JP1 = IN, NOAUTO (SPARE) = IN**

**MODC = Out, JP2 = do not care, see COM Ports.**

2. Connect one end of the supplied 9-pin serial cable to an available serial COM port on your PC. Connect the other end of the cable to the P-COM port on the CML12Sxxx board.
3. Apply power to the board by plugging in the power adapter that came with the system.
4. If everything is working properly, you should see a message to "**PRESS KEY TO START MONITOR...**" in your terminal window. Press the ENTER key and you should see:

```
Axiom MON12 - HC12 Monitor / Debugger V256.x
Type "Help" for commands...

> _
```

5. Your board is now ready to use! If you do not see this message prompt, or if the text is garbage, see the **TROUBLESHOOTING** section at the end of this manual.

## Support Software

There are many programs and documents on the included HC12 support CD you can use with the CML12Sxxx board. You should install what you want from the main menu then browse the disk and copy what you like to your hard drive.

At minimum, you should install the AxIDE program. This provides the flash programming utility and communication with the board via the COM port and the supplied serial cable. This program includes a simple terminal for interfacing with other programs running on the CML12Sxxx and information from your own programs that send output to the serial port.

Also on the disk are free assemblers AS12 and MCU-EZ, the open source GNU C/C++ compiler tools for HC11/12, example source code, and other useful software. The introductory tutorial in this manual uses the free AS12 assembler integrated into the AxIDE program. This is a simple assembler with limited capability. For a more powerful assembly tool, install the Motorola MCUEZ program from the CD. This will allow you to use PAGED program memory in your application.

## Software Development

Software development on the CML12Sxxx can be performed using either the MON12 monitor installed in internal FLASH of the MCU, a third party debugger (Debug12, NoICE, CodeWarrior, etc.) or a Background Debug Module (BDM) connected to the BDM PORT connector. Any of these tools can be used to assist in creating and debugging your program stored in RAM (see **Memory Map**).

After satisfactory operation running under a debugger, your program can be written to Internal Flash Memory using the included programming utilities. The Mon12 firmware in the MCU flash provides the interrupt vectors in Ram memory and an Autostart feature to launch your application. Your program may then run automatically whenever the board is powered on or RESET is applied.

## TUTORIAL

This section was written to help you get started developing software with the CML12SXXX board. Be sure to read the rest of this manual as well as the documentation on the disk if you need further information.

The following sections take you through the complete development cycle of a simple "hello world" program, which sends the string "Hello World" to the serial port.

### Creating Source Code

You can write source code for the CML12SXXX board using any language that compiles to Motorola 68HC12 instructions. Included on the software disk is a free Assembler, AS12.

You can write your source code using any ASCII text editor. You can use the free EDIT, WordPad, or Notepad programs that come with your computer. Note that the source file must be simple ASCII text without any document formatting added. Once your source code is written and saved to a file, you can assemble or compile it to a Motorola S-Record (hex) format. This type of output file usually has a .MOT, .HEX or .S19 file extension and is in a format that can be read by the programming utilities and programmed into the CML12SXXX board.

It is important to understand the development board's use of Memory and Addressing when writing source code so you can locate your code at valid addresses. For example, when in debug mode, you should put your program CODE in External RAM. In assembly language, you locate the code with ORG statements in your source code. Any lines following an ORG statement will begin at that ORG location, which is the first number following the word ORG, for example: **ORG \$4000**. You must start your DATA (or variables) in a RAM location unused by your program, for example: **ORG \$1000**.

In "debug mode" you'll be using a debugger utility (Mon12, NoICE, etc) which will handle initialization, interrupts vectors (reset, timers, etc), and the STACK. When finished debugging, you must add code to your application to handle the initialization of the CPU, STACK and possibly the Interrupt vectors. Some initialization is required to set the bus frequency, bus mode, internal EEPROM and Flash memory programming clock rates, and others, see the CML-INIT.ASM file for a sample. Set the stack at the top of your available internal RAM below the Ram interrupt vector table, for example \$3F80, in assembly this would be **LDS #3F80**. Also install the RESET vector address in the Auto Start area, see the chapter in this manual.

If you are applying a software development tool that also provides a BDM cable interface to the board, the monitor installed in the flash is not required. The BDM software tools may have the capability to erase and program the flash memory. If this is the case, you may develop code in the external ram memory or internal flash without applying the monitor resources. The MON12 S record is provided on the support CD to program into the flash if desired. The BDM will allow locating programs in memory and applying resources reserved for the monitors.

A look at the example programs on the disk can make all of this clearer. If you're using a compiler instead of an assembler, consult the compiler documentation for methods used to locate (MAP) your code, data and stack.

### Assembling source code

An example program called "HELLO.ASM" is provided under the \EXAMPLES\CML12 directory of the CD and if you installed AxIDE, under that programs \EXAMPLE directory. You must use the example for the MCU type installed on the CML12Sxxx board. For example use the CML12S-DP256 example on the DP256 version board.

You can assemble source code by using the AxIDE "BUILD" button or command line tools under a DOS prompt by typing:

```
AS12 HELLO.ASM -L HELLO
```

Most compilers and assemblers allow many command line options so using a MAKE utility or batch file is recommended if you use this method. Run AS12 without any arguments to see all the options, or see the AS12.TXT file on the disk.

The utility software, AxIDE, provided with this board contains a simple interface to this assembler. Use it by selecting "Build" from its menu. This will prompt you for the file to be assembled. **NOTE:** You must select your board from the pull down menu first, or it may not build correctly.

**DO NOT** use long path or file names (> 8 characters). The free assembler is an older DOS based tool that does not recognize them.

If there are no fatal errors in your source code, 2 output files will be created:

**HELLO.S19** a Motorola S-Record file that can be loaded or programmed into memory  
**HELLO.LST** a common listing file which provides physical address information with resulting opcode and operand information. Warnings and error messages are provided with a summary at the end of the file.

The listing file is especially helpful to look at when debugging your program. If your program has errors, they will be displayed in the listing or fatal errors will prevent output from being generated. The end of the listing file generally provides a count of errors or warnings in the file.

If you prefer a windows integrated programming environment, try the Motorola MCU-EZ tools. Refer to the MCU-EZ documentation on the disk for more information.

Also, a port for the free GNU C compiler and tools for the HC12 is available on the CD under \Shareware and also online at [www.gnu-m68hc11.org](http://www.gnu-m68hc11.org). Note that this version does not support HC12 Paging operation, check the web site for updates.

## Running your application

After creating a Motorola S-Record file you can "upload" it to the development board for a test run. The provided example "HELLO.ASM" was created to run from external RAM so you can use the MON12 Monitor to test it without programming it into Flash.

If you haven't done so already, verify that the CML12Sxxx board is connected and operating properly by following the steps under "GETTING STARTED" until you see the Mon12 prompt, then follow these steps to run your program:

1. Press and release the RESET button on the CML12Sxxx board. You should see the PRESS ANY KEY message. Hit the return key ↵ to get the monitor prompt.
2. Type **LOAD** ↵  
This will prepare Mon12 to receive a program.
3. Select Upload and when prompted for a file name select your assembled program file in s-record format that was created in the previous section called: **HELLO.S19**  
Your program will be sent to the board through the serial port.
4. When finished loading you will see a done message and the > prompt again. Type **GO 4000** ↵  
This tells MON12 to execute the program at address \$4000 hex, which is the start of our test program.
5. If everything is working properly you should see the message "Hello World" echoed back to your terminal screen. Press RESET to return to the monitor.
6. If you do not get this message, see the **TROUBLESHOOTING** section in this manual

You can modify the hello program to display other strings or do anything you want. The procedures for assembling your code, uploading it to the board and executing it remain the same. MON12 has many features such as breakpoints, memory dump and modify and simple program trace (no redirect of the PC is followed). Type **HELP** at the MON12 prompt for a listing of commands or consult the Mon12 documentation on the disk for more information.

For a more powerful debugger with many advanced features such as source level debugging, you can use the NoICE debugger software. A full-featured demo version is provided on the CD, which you can use to get started. **NOTE:** To use this program instead of MON12 you must set the Autostart, see the NOICE chapter for details.

## Programming HCS12 Flash EEprom

After debugging, you can program your application into Flash Memory so it executes automatically when you apply power to the board as follows:

1. Make a backup copy of HELLO.ASM then use a text editor to modify it.
2. Remove the comment ';' character before one of the following lines to initialize the stack pointer which is necessary when running outside of a debugger:  

```
LD8    #03F80    ; initialize stack location...
```
3. Re-Assemble HELLO.ASM as described in the "Assembling Source Code" section.
4. Select **Program** from the AxIDE menu and follow the message prompts. When prompted for a file name, enter the new HELLO.S19 file.
5. Press the RESET button on the board before clicking OK. When prompted to Erase, choose Yes.
6. When finished programming, Reset the board to get the Monitor prompt again. Use the monitor **AUTO** command to set the Autostart Reset vector:

```
>AUTO 4000 ↵
AutoStart ON, effective address = 4000
>
```

7. Verify AUTO OFF option jumper is not installed. (Spare jumper on revision C boards)
8. RESET or re-apply Power to the board. Your new program should start automatically and the "Hello World" prompt should be displayed in the terminal window.

To return to the MON12 monitor program, install the AUTO OFF option jumper then press RESET. Execute the monitor command NOAUTO to disable the Autostart and allow removal of the Auto Off option jumper for normal operation.

## MON12 OPERATION

Mon12 is an embedded monitor / debug utility that allows loading a compiled software program (S record) into Ram memory for testing and debug. The monitor may control the execution of the software by applying the SWI software interrupt service. Other features allow memory and register examination or modification.

Communication with the monitor is provided on the HCS12 SCI0 serial port or COM port on the development board. Default settings are 9600 baud with 8/n/1 bit settings. Flow control is not provided so the host PC communication software should be set to None or Hardware flow control. AxIDE utility software is recommended for use on a windows based host PC.

The monitor relies on resources from the HCS12 target to provide the monitor environment. The resources include 16K bytes of flash memory and 512 bytes of internal ram memory. The user must respect the monitor's memory map when applying the monitor to help debug code. Restricted memory areas:

**Monitor Program space:** 0xC000 - 0xFFFF Flash or Flash Page \$3F.

**Monitor Data space:** 0x3E00 - 0x3FFF, Internal Ram.

**Monitor Console:** COM Port and SCI0.

**Monitor Autostart:** 0xFEC - 0xFEF, Internal EEProm.

Monitor application provides for redirection of interrupt vectors through the ram based interrupt table, initialization of SCI0 serial port, initialization of HCS12 flash and EEProm programming clock rates, initialization of 8 MHz E clock from 4Mhz reference crystal, and detection of auto start enabled operation. The HCS12 memory map is fixed under monitor operation.

The monitor provides for interrupt vectors in the monitor data space from 0x3F8A - 0x3FFD. The vectors are in the same order as the default hardware table for the HCS12 located at address 0xFF8A - 0xFFFFD (see table). The Reset vector is reserved, user should apply Auto Start for application starting from Reset.

### MON12 operation notes:

1. CML12S-DP256 monitor application configures target HCS12 for 8MHz E clock, lower flash block (page \$3E) disabled from memory map, and external access clock stretch set to 3 cycles. User can increase clock speed in application by modifying PLL control and setting new baud rate for serial port. Defaults will return whenever monitor is Reset.
2. Mon12 will not trace into interrupts. To trace an interrupt service set a breakpoint in the service routine and then trace.
3. Mon12 trace is limited to expecting the next linear address. Program counter modification, branches, calls, or subroutines will not trace correctly.
4. Monitor start-up procedure:

A) Determine if Auto Start is enabled and proceed to vector if not a value of \$FFFF.

B) Set Stack, Initialize memory map and SCI0 port and send prompt.

C) Receive first character from Console port and execute monitor if ASCII text / command, else start utility mode for programming services.

## Mon12 Monitor Commands

<b>AUTO</b> [<Address>]	Enable Auto start, address is the vector
<b>NOAUTO</b>	Disable Auto start
<b>BF</b> <StartAddress> <EndAddress> [<data>]	Fill memory with data
<b>BR</b> [<Address>]	Set/Display user breakpoints
<b>BULK</b>	Erase entire on-chip EEPROM contents
<b>CALL</b> [<Address>]	Call user subroutine at <Address>
<b>G</b> [<Address>]	Begin/continue execution of user code
<b>HELP</b>	Display the Mon12 command summary
<b>LOAD</b> [P]	Load S-Records into memory, P = Paged S2
<b>MD</b> <StartAddress> [<EndAddress>]	Memory Display Bytes
<b>MM</b> <Address>	Modify Memory Bytes (8 bit values)
<b>MW</b> <Address>	Modify memory Words (16 bit values)
<b>MOVE</b> <StartAddress> <EndAddress> <DestAddress>	Move a block of memory
<b>RD</b>	Display all CPU registers
<b>RM</b>	Modify CPU Register Contents
<b>STOPAT</b> <Address>	Trace until address
<b>T</b> [<count>]	Trace <count> instructions

## MON12 Interrupt Support

All interrupt services under MON12 are provided through the ram vector table, **see Table 2**. Each location in the table is initialized to a value of \$0000 to cause the trap of an unscheduled interrupt. Any nonzero value will allow the interrupt to proceed to the user's service routine that should be located at the provided address value. Interrupt service delay is plus 21 cycles over standard interrupt service.

To use vectors specified in the table, the user must insert the address of the interrupt service routine during software initialization into the ram interrupt table. For an example, for the IRQ vector, the following is performed:

Example:   IRQ Service routine label = IRQ\_SRV  
               Ram Vector Table address is defined in table below, IRQ vector definition:  
               VIRQ EQU \$3EF2 ; define ram table vector location

Place IRQ service routine address in the table:  
               MOVW     #IRQ\_SRV,VIRQ

This vector initialization should remain after debug when auto start will be applied for launching the user's application. Note that the user interrupt service routines must be located in the \$4000 - \$7FFF address range for correct operation. See Autostart for more details.



## MON12 and NOICE Memory Map

ADDRESS	TYPE MEMORY	MEMORY APPLICATION
\$C000 - \$FFFF	FLASH	MON12, NOICE, and Utility firmware located in internal flash, Page \$3F.
\$8000 - \$BFFF	External Ram	User Paged Program Memory space, pages \$20 - \$2E. Note: Pages \$30 - \$3F reside in the internal flash.
\$4000 - \$7FFF	External Ram	User Program Memory, emulate fixed page \$3E.
\$3F8C - \$3FFD	Internal Ram	Ram Interrupt Vector Table
\$3E00 - \$3F8B	Internal Ram	Monitor reserved ram memory. Stacks and variables.
\$1000 - \$3DFF	Internal Ram	User Internal Ram memory
\$0400 - \$0FEB	Internal EEprom	User EEprom memory, Monitor reserves \$FEC - \$FEF for Autostart, user should avoid \$FF0 - \$FFF memory use.
\$0000 - \$03FF	HCS12 Registers	Monitor or user access to control registers.

## NOICE OPERATION

NOICE is a development software provided by [www.NOICEdebugger.com](http://www.NOICEdebugger.com). NOICE provides a development environment that is supported by the NOICE host PC software. This development environment has the capability to provide symbolic debug for C source codes and compilers for a low cost. A fully functional software version is available on the support CD that will operate in demonstration mode. The user should register the software and download the latest version from the above web site to get full support. See the NOICE documentation for details.

The CML12S-DP256 provides the NOICE debug monitor kernel as a subset of the MON12 monitor in reserved flash memory. User may apply the NOICE development system by setting the MON12 Autostart for the \$F800 vector, reset the board and launch the NOICE host software on the PC. The NOICE monitor kernel applies the same resources, memory map, and ram interrupt table as the MON12 monitor. NOICE operation notes:

**Baud Rate** = 19.2K baud 8/n/1

**E clock frequency** = 24 MHz

## BDM OPERATION

The CML12S-DP256 board will emulate supported HC12 device internal flash memory in external ram. This feature allows BDM (Background Debug Modules) such as the AX-BDM12 to load and control the execution of code being developed without the necessity of the internal flash memory being programmed many times during the development process. This feature improves updating time and allows the use of many software breakpoints instead of being limited to only 2 hardware breakpoints.

Operation Notes for BDM use:

- 1) CML12S-DP256 **MODC Option Jumper** should be installed if a BDM is connected to the BDM Port. Default Mode is single-chip so the MODC option installed will force Special Single-chip Mode on Reset.
- 2) The BDM initialization of the HC12 should set the correct operating MODE (Expanded Wide for memory access). The EME, EMK, LSTRB, RW, ROMEN and Stretch configuration bits should be set for proper external memory access operation. The Axiom support CD contains sample set-up macros for the AX-BDM12.
- 3) While using the BDM, the user has full control over the memory map and hardware resources of the HCS12. The no resources are required to be reserved for monitor use and the user can apply the actual HCS12 interrupt vector table located at 0xFF8C - 0xFFFF.

## AUTOSTART

The MON12 Monitor allows an Autostart operation to launch user applications programmed into the HCS12 internal flash fixed page (\$3E) addresses 0x4000 - 0x7FFF from Reset. The Autostart mask and vector are stored in the nonvolatile internal EEprom at addresses \$FEC - \$FEF. The monitor provides special commands, **AUTO** and **NOAUTO**, to enable and disable the Autostart on the next Reset sequence. After an Autostart is enabled with a valid user vector, user application code will be started after Reset instead of the monitor or utility programs. To recover monitor operation after Autostart has been enabled, the **AUTO OFF** (Spare option on Revision C boards) option jumper can be installed or a low level applied to the XIRQ signal and Reset applied.

User application must perform all initialization including Stack setting, hardware startup, and external memory bus enable if needed, when the Autostart is applied. MON12 Ram Interrupt Vector table must also be applied in the same manner as under MON12 supervision or application interrupts will be trapped instead of serviced. See the CML12S.asm file for sample start-up initialization code.

Developing an application under MON12 or NOICE for Autostart should follow these steps:

- 1) Follow the MON12/ NOICE memory map and apply startup initialization and interrupt service routines in the 0x4000 - 0x7FFF memory area.

- 2) After development by applying ram memory program pages \$20 - \$2D, user should relocate the paged program code to internal flash pages \$30 - \$3D for programming into the flash memory. The user code in memory area 0x4000 - 0x7FFF will translate to the lower fixed flash page \$3E for programming operations. User variables and stack, as well as interrupt vectors should stay in the internal ram area 0x1000 - 0x3E80 (monitor stack and variables not needed). Then set the Autostart vector for application launching.
- 3) If the Autostart application fails to start after programming, user should review all initialization and memory mapping first. Make sure the AUTO OFF (Spare) Option jumper is idle or open. If the application applies the XIRQ interrupt, the interrupt must be idle (high level) during any Reset sequence. Hardware may need to be applied if XIRQ signal level cannot be guaranteed high during Reset.
- 4) To perform a test Autostart and apply the external ram for program space the following precaution should be observed:
 

Expanded Wide Mode bus operation must be enabled from internal Ram space before access to the external ram can be performed. Use CML12S.asm file for an example and locate the PEAR/MODE Register write in internal ram space 0x1000 - 0x3F80. Program pages \$20 - \$2D should be applied. Code must be loaded and tested without powering down the development board (use Reset Switch).

## OPTIONS and JUMPERS

### MEM\_EN

The MEM\_EN option jumper is installed by default and enables the external ram memory on the expanded HCS12 address and data bus. Removing the MEM\_CS option jumper will allow single-chip I/O port type operation of HCS12 ports A, B, E, and K (no bus enabled) without external memory interference.

### ECS

The ECS option installed enables the Emulation Chip Select signal from the HCS12 to drive the upper address lines from HCS12 Port K to the external Ram on the CML12S board. With the option open or idle, only the linear 64K byte address map is available on the external address / data bus. ECS installed is required to emulate flash program pages in the external ram memory.

### MODC

The MODC option jumper provides Special Mode enable during Reset. This option must be open or idle when operating with the MON12 or NOICE monitors. If a BDM cable is applied to BDM port, the MODC option must be installed to enable Special Mode. Failure to install the MODC jumper during BDM application may cause communication problems with the host.

## AUTO OFF / spare

The AUTO OFF (Spare on REV C. board) option jumper installed defeats the Autostart operation so the MON12 monitor will provide a command prompt. The jumper applies a ground potential to the XIRQ\* interrupt line. User should only install the jumper to restore monitor operation, perform the MON12 NOAUTO command to disable the Autostart, and remove or idle the jumper. MON12 operation will then be provided on subsequent Reset conditions.

## MODE

The MODE option jumper is not installed on the CML12S-DP256 board and is hard connected by circuit copper trace for Single-chip Mode operation of the CPU. Both the MODA and MODB signals are terminated by this option. Due to the restriction that the HCS12 internal flash memory is the only nonvolatile program memory provided on the board, single Chip Mode is default. All other Modes can be enabled under software control from this mode of operation.

The MODE option jumper may be installed by the user by cutting the hard trace and applying 2 header pins with a shunt jumper. With the shunt jumper removed, the Reset mode will then be Normal Expanded Wide. (Note: mask set 1K79X and earlier will not fetch the Reset vector from external memory in this mode).

### OSC\_SEL

The OSC\_SEL option jumper is not installed on the CML12S-DP256 board. The default configuration is for the provided 4MHz reference crystal to provide the HCS12 oscillator. If the user requires an external clock to be applied, two header pins and shunt jumper can be applied to select the alternate clock source. User should refer to the HCS12 User Guide and CML12S board schematic for proper application of the external clock.

### ROM\_OFF

The ROM\_OFF option jumper is not installed on the CML12S-DP256 board. The default configuration is that the internal flash memory of the HCS12 is enabled at Reset. The user must add external nonvolatile memory to the CML12S board to take advantage of this option. If the external memory is applied, the user may install the two header pins and shunt jumper to select internal or external memory use form Reset.

## JP1 and JP2

JP1 and 2 option jumpers provide an easy method of connecting or isolating the HCS12 SCI0 and SCI1 serial channel RXD pins respectively from the provided on-board RS232 transceiver. To apply the RXD pins on the SCI channels for other user applications requires that the transceiver driver be removed from the HCS12 pin. User may then apply signals to the respective pins at the MCU PORT connector without driver conflict. Please note that the on-board monitor(s) require HCS12 SCI channel 0 (JP1 installed) for user interface.

## CUT-AWAY OPTIONS 1 - 6

CUT-AWAY options allow the user to disconnect dedicated HCS12 I/O port resources from development board peripherals. The CUT-AWAY options also allow for establishing the connection again by installing surface mount 1206 size 0 ohm resistors or mod wire with the use of a soldering iron. Normal operation of the development board generally does not require any manipulation of the CUT\_AWAY options.

**#1 Cut-Away:** HCS12 Port S5/MOSI signal to the LCD\_PORT shift register.

**#2 Cut-Away:** HCS12 Port S7/SS0 signal to the LCD\_PORT shift register.

**#3 Cut-Away:** HCS12 Port S6/SCK signal to the LCD\_PORT shift register.

**#4 Cut-Away:** HCS12 Oscillator Crystal ground, if another crystal is applied by the user this connection may require a capacitor to be installed. Refer to the HCS12 CGM module information.

**#5 Cut-Away:** HCS12 Port M0/CAN\_RXD0 signal to the CAN port transceiver.

**#6 Cut-Away:** CAN Port Transceiver enable connection to ground. This connection enables the CAN Port transceiver output to the CAN bus at all times. If the user wants to apply output enable or slew rate control to the transceiver, this option should be cut and 1206 size resistor applied for slew rate or a HCS12 I/O port applied for output enable control. See the PCA82C250 data sheet for application information.

## PORTS AND CONNECTORS

### TB1 and J1 Power

The TB1 and J1 connectors provide power input to the board or if J1 is used for input, TB1 maybe used to source additional circuitry. The J1 power jack accepts a standard 2.0 ~ 2.1mm center barrel plug connector (positive voltage center) to provide the +VIN supply of +7 to +20 VDC @ 80ma minimum (+9VDC nominal). TB1 provides access to the +VIN, GND (power ground), HCS12 core VDD, and +5V power supplies. The CML12Sxxx power supply will provide 50ma of +5V for user application. +VIN input power should only be applied by J1 or TB1, not both or a supply conflict may occur and the CML12Sxxx board could be damaged. The VDD supply is for reference or external 2.5V input only and should not be loaded by external circuitry or damage to the HCS12 device may occur.

## MCU\_PORT

+5V	60	59	GND
PT7	58	57	PT6
PT5	56	55	PT4
PT3	54	53	PT2
PT1	52	51	PT0
** PK0	50	49	PK1 **
** PK2	48	47	PK3 **
** PK4	46	45	PK5 **
GND	44	43	+5V
PP1	42	41	PP0
PP3	40	39	PP2
PP5	38	37	PP4
PP7	36	35	PP6
** PM1	34	33	PM0 **
PM3	32	31	PM2
PM5	30	29	PM4
PM7	28	27	PM6
PJ1	26	25	PJ0
PJ7	24	23	PJ6
** PS7	22	21	PS6 **
** PS5	20	19	PS4 **
** PS3	18	17	PS2 **
** PS1	16	15	PS0 **
GND	14	13	+5V
GND	12	11	VREGEN
** PB7/D7	10	9	PB6/D6 **
** PB5/D5	8	7	PB4/D4 **
** PB3/D3	6	5	PB2/D2 **
** PB1/D1	4	3	PB0/D0 **
GND	2	1	+5V

The **MCU\_PORT** provides access to the peripheral features and I/O lines of the HCS12.

\*\* Note signals with alternate connections on the development board:

PB0 - 7 [D0 - 7] provide address / data on the expanded HCS12.

PK0 - 5 [XA14 - XA19] provide high order paged address lines on the expanded HCS12.

PM0 - 1 [CAN\_RXD0, TXD0] CAN channel 0 to CAN Port transceiver.

PS0 - 1 [COM Port RXD0, TXD0]

PS2 - 3 [JP3 Port RXD1, TXD2]

PS4 - 7 [SPI Port] provides LCD\_PORT serial interface.

## ANALOG PORT

PAD0/AN0	1	2	PAD8/AN8
PAD1/AN1	3	4	PAD9/AN9
PAD2/AN2	5	6	PAD10/AN10
PAD3/AN3	7	8	PAD11/AN11
PAD4/AN4	9	10	PAD12/AN12
PAD5/AN5	11	12	PAD13/AN13
PAD6/AN6	13	14	PAD14/AN14
PAD7/AN7	15	16	PAD15/AN15
VRH	17	18	VRL
VDDA	19	20	GND

The **ANALOG** port provides access to the Port AD0 and Port AD1 Analog-to-Digital input lines.

**PAD0 – PAD15** HC12 Port AD0-15 is an input port or AN0 - AN15 A/D Converter inputs.

**VRH / VRL** HC12 A/D Converter Reference Pins. See HCS12 A/D User guide. To provide an external reference voltage, R3 and R4 need to be removed to apply external VRH or VRL respectfully. See schematic.

## BUS\_PORT

GND	1	2	D11/PA3
PA2/D10	3	4	D12/PA4
PA1/D9	5	6	D13/PA5
PA0/D8	7	8	D14/PA6
A0	9	10	D15/PA7
A1	11	12	A2
A10	13	14	A3
OE*	15	16	A4
A11	17	18	A5
A9	19	20	A6
A8	21	22	A7
A12	23	24	A13
WE*	25	26	A14
PE3/LSTRB*	27	28	A15
PE5/MODA	29	30	PE7/NOACC **
PE6/MODB	31	32	PE1/IRQ*
+5V	33	34	PE0/ XIRQ*
PE2/RW	35	36	RESERVED
PE4/ECLK	37	38	RESERVED
GND	39	40	RESET*

The **BUS\_PORT** supports off-board memory devices while the HCS12 is in expanded mode.

**PA0/D8 - PA7/D15** High Byte Data Bus in Wide Expanded Mode. Port A in Single Chip Mode.

**A0 - A15** Latched Memory Addresses 0 to 15.

**OE\*** Memory Output Enable signal, Active Low. Valid with ECLK and R/W high.

**WE\*** Memory Write Enable signal, Active Low. Valid with ECLK high and R/W low.

**RESET\*** HCS12 active low RESET signal.

## KEYPAD / PORT H

The **KEYPAD / PORT H** connector provides interface for the HCS12 port H or applying a keypad such as the Axiom Mfg. HC-KP. When applied as a **KEYPAD** connector, the interface is for a passive 4 x 4 matrix (16 key) keypad device.

1	PH0	This interface is implemented as a software key scan. Pins PH0-3 are used as column drivers which are active high outputs. Pins PH4-7 are used for row input and will read high when their row is high.
2	PH1	
3	PH2	
4	PH3	See the file <b>Key12Dx.ASM</b> for an example program using this connector.
5	PH4	
6	PH5	
7	PH6	
8	PH7	

## P\_COM1 and P\_COM2

1	1	6	The <b>COM-1</b> port has a Female DB9 connector that interfaces to the HCS12 internal SCI0 serial port via the U11 RS232 transceiver. It uses a simple 2 wire asynchronous serial interface and is translated to RS232 signaling levels. <b>1,4,6 connected and 7,8 connected</b>
TXD0	2	6	
RXD0	3	7	
	4	8	
GND	5	9	

JP1 will isolate the SCI0 RXD pin from the transceiver.

The 1,4,6,7,8, and 9 pins provide RS232 flow control and status. These are connected on the bottom of the development board to provide NULL status to the host. User may isolate pins and provide flow control or status connection to the host by applying HCS12 I/O signals and **RS232 level conversion**.

## P\_COM2

**P\_COM2** is a 3 pin header that provides the HCS12 SCI1 serial port translated to RS232 signal levels. A solder cup DB9 style connector may be installed with wires and connector to apply this channel. JP2 option will isolate the SCI RXD pin from the transceiver.

**P\_COM2 pin connections:**

Pin 1 = TXD

Pin 2 = RXD

Pin 3 = GND / common

## CAN PORT

This port provides a CAN Bus interface associated with HCS12 CAN channel 0. The port has a CAN Transceiver (Philips PCA82C250) capable of up to 1M Baud data rate. The user may isolate the HCS12 CAN channel 0 from the transceiver by CUT-AWAY option 5.

### CAN Port Connections

1	GND	The CAN Port connector provides an interface to the MSCAN12 channel 0 in the HCS12 microcontroller.
2	CAN-H	
3	CAN-L	
4	+5V	

### CAN BUS TRANSMIT ENABLE

The CAN port transceiver transmit driver is enabled for maximum drive and minimum slew rate by default. The drive and slew rate may be adjusted by cutting CUT-AWAY #6 and adding a 1206 size surface mount resistor, see the PCA82C250 data sheet for more information.

CAN Bus transceiver transmit enable control can be applied to the port by the RS tie pad. The user should select an available HCS12 I/O port to perform the transmit enable function and connect it from the MCU\_PORT pin to RS pad as required. **The CUT\_AWAY #6 must be open to apply transmit enable control.** The transmit enable signal to the CAN transceivers is active logic low.

## CAN BUS TERMINATION

The CAN port provides RC11,12, and 13 1206 SMT size termination resistors on the bottom of the CML12Sxxx board that are not installed at the factory. The termination resistors provide optional bias and termination impedance for the CAN bus connected to the CAN Port. Type of wire media, data rate, length of wire, and number of CAN bus nodes can all effect the requirement or value of the termination for the CAN bus. User should refer to particular application for termination requirements.

**RC11 CAN-H Bias Resistor:** Provides bias to ground potential.

**RC13 CAN-L Bias Resistor:** Provides bias to +5V potential.

**RC12 CAN Termination Resistor:** Provides end point termination between CAN-H and CAN-L signal.

## P1 - P4 HCS12 Header Ring

P1 - P4 provide a header ring for all I/O of the HCS12 device. These connectors are not installed. User should refer to the CML12S board schematic diagram for connector pin connections. All HCS12 I/O is available from the other I/O Ports on the board.

## LCD\_PORT

The LCD\_PORT interface is connected to the HCS12 SPI-0 port and applies a serial shift register to convert the data to parallel interface for LCD input. This is required due to the fast timing characteristics of the HCS12 data bus and the slow timing of the standard LCD Modules. Example LCD Port assembly language driver software is provided on the support CD to demonstrate typical LCD module operation using this technique.

The interface supports all OPTREX™ DMC series and similar displays with up to 80 characters in 4 bit bus mode and provides the most common pinout for a dual row rear mounted display connector. The LCD module VEE or contrast potential is 0 Volts on this board. The LCD module type should be TN (Standard Twist) style and Reflective to support this VEE potential. The Axiom Mfg. HC-LCD is also compatible. The LCD Module is configured in a Write only mode, it is not possible to read current cursor position or the busy status back from the module.

### LCD\_PORT Connector

+5V	2	1	GND	SPI data bit definitions to LCD Port:
RS	4	3	VEE-GND	D0 - D3 = DB4 - 7, LCD data
EN	6	5	R/W-GND	D4 - D5 = Spare pins S1 and S2, not connected
DB1	8	7	DB0	D6 = RS, 0 = LCD Command, 1 = LCD Data
DB3	10	9	DB2	D7 = EN, 1 = LCD enable.
DB5	12	11	DB4	DB0 -DB3 are not applied and have 10K pull-down
DB7	14	13	DB6	resistance.

NOTES:

- 1) The LCD write requires 3 SPI transfers. Transfer 1 provides data 0 - 3 and RS (register select) value. Transfer 2 provides the same data with the EN (D7) bit set. Transfer 3 provides same data with the EN bit clear.
- 2) Resistor R25 can be removed to apply and external VEE potential.
- 3) CUT-AWAY 1 - 3 provide a means to isolate the LCD Port from the HCS12 SPI channel.

## BDM PORT

The BDM port is a 6 pin header compatible with the Motorola Background Debug Mode (BDM) Pod. This allows the connection of a background debugger for software development, programming and debugging in real-time without using HC12 I/O resources.

BGND	1	2	GND	See the HC12 Technical Reference Manual for complete documentation of the BDM.
	3	4	/RESET	
	5	6	+5V	

A Background Debug Module is available from the manufacturer.

## TEST POINTS

The following test points are provided on the development board:

**EXTAL :** HCS12 oscillator or external clock input pin.

**XTAL :** HCS12 oscillator output pin.

**XFC :** HCS12 PLL reference voltage and filter.

**VDDPLL :** HCS12 PLL voltage source test point.



## TROUBLESHOOTING

The CML12SXXX board is fully tested and operational before shipping. If it fails to function properly, inspect the board for obvious physical damage first. Ensure that all IC devices in sockets are properly seated. Verify the communications setup as described under GETTING STARTED and see the **Tips and Suggestions** sections following for more information.

The most common problems are improperly configured communications parameters, and attempting to use the wrong COM port.

1. Verify that your communications port is working by substituting a known good serial device or by doing a loop back diagnostic.
2. Verify option jumpers JP1 is installed and MODC is open / idle.
3. Verify Autostart is not enabled. Apply a ground level to the XIRQ signal on the BUS\_PORT and press the Reset switch. If the monitor prompts, erase the internal EEPROM by performing a BULK command or disable the Autostart by following the procedure in the Autostart chapter.
4. Verify the power source. You should measure a minimum of 9 volts between the GND and +VIN connections on the TB1 power connector with the standard power supply provided.
5. If no voltage is found, verify the wall plug connections to 115VAC outlet and the power connector.
6. Verify the logic power source. You should measure +5 volts between the GND and +5V connections on the TB1 power connector. If the +VIN supply is good and this supply is not +5V, immediately disconnect power from the board. Contact [support@axman.com](mailto:support@axman.com) by email for instructions and provide board name and problem.
7. Disconnect all external connections to the board except for COM1 to the PC and the wall plug.
8. Make sure that the RESET line is not being held low. Check for this by measuring the RESET Signal on the BUS\_PORT.
9. Verify the presence of a 4MHz square wave at the EXTAL pin or 8MHz E clock signal if possible.
10. Contact [support@axman.com](mailto:support@axman.com) by email for further assistance. Provide board name and describe problem.

## Tips and Suggestions

Following are a number of tips, suggestions, and answers to common questions that will solve many problem users have with the CML12SXXX development system. You can download the latest software from the Support section of our web page at:

[www.axman.com](http://www.axman.com)

### Utilities

- If you're trying to program memory or start the utilities, make sure all jumpers are correct.
- Be certain that the data cable you're using is bi-directional and is connected securely to both the PC and the board. Also, make sure you are using the correct serial port.
- Make sure the correct power is supplied to the board. You should only use a 9 volt, 200mA minimum adapter or power supply. If you're using a power strip, make sure it is turned on.
- Make sure you load your code to an address space that actually exists. See the Memory Map if you're not sure. The MEM\_EN and ECS options change the memory map.
- If debugging under Mon12, make sure you're not over-writing internal RAM used by it.
- If you're running in a multi-tasking environment (such as Windows™) close all programs in the background to be certain no serial conflict occurs.

### Code Execution

- Under Mon12, breakpoints may not be acknowledged if you use the CALL command. You should use one of the GO command instead.
- Check the Autostart mask and reset vector located in EEPROM at 0xFEC - 0xFEFF. These 2 words contain the enable mask and address where user application execution will begin when the unit is powered on.
- When running your code stand-alone, you must initialize ALL peripherals used by the micro, including the Stack, Serial Port, and pseudo Interrupt vectors etc.
- You must either reset the COP watchdog timer in the main loop of your code or disable it when not running under Mon12 or BDM mode. The micro may enable this by default and if you don't handle it your code will reset every few 100ms.

**TABLE 1: LCD Command and Character Codes**

Command codes are used for LCD setup and control of character and cursor position. All command codes are written to LCD panel address \$B5F0. The BUSY flag (bit 7) should be tested before any command updates to verify that any previous command is completed. A read of the command address \$B5F0 will return the BUSY flag status and the current display character location address.

Command	Code	Delay
Clear Display, Cursor to Home	\$01	1.65ms
Cursor to Home	\$02	1.65ms
Entry Mode:		
Cursor Decrement, Shift off	\$04	40us
Cursor Decrement, Shift on	\$05	40us
Cursor Increment, Shift off	\$06	40us
Cursor Increment, Shift on	\$07	40us
Display Control:		
Display, Cursor, and Cursor Blink off	\$08	40us
Display on, Cursor and Cursor Blink off	\$0C	40us
Display and Cursor on, Cursor Blink off	\$0E	40us
Display, Cursor, and Cursor Blink on	\$0F	40us
Cursor / Display Shift: (nondestructive move)		
Cursor shift left	\$10	40us
Cursor shift right	\$14	40us
Display shift left	\$18	40us
Display shift right	\$1C	40us
Display Function (default 2x40 size)	\$3C	40us
Character Generator Ram Address set	\$40-\$7F	40us
Display Ram Address and set cursor location	\$80-\$FF	40us

**LCD Character Codes**

\$20	Space	\$2D	-	\$3A	:	\$47	G	\$54	T	\$61	A	\$6E	n	\$7B	{
\$21	!	\$2E	.	\$3B	;	\$48	H	\$55	U	\$62	B	\$6F	o	\$7C	
\$22	"	\$2F	/	\$3C	{	\$49	I	\$56	V	\$63	C	\$70	p	\$7D	}
\$23	#	\$30	0	\$3D	=	\$4A	J	\$57	W	\$64	D	\$71	q	\$7E	>
\$24	\$	\$31	1	\$3E	}	\$4B	K	\$58	X	\$65	E	\$72	r	\$7F	<
\$25	%	\$32	2	\$3F	?	\$4C	L	\$59	Y	\$66	F	\$73	s		
\$26	&	\$33	3	\$40	Time	\$4D	M	\$5A	Z	\$67	G	\$74	t		
\$27	'	\$34	4	\$41	A	\$4E	N	\$5B	[	\$68	H	\$75	u		
\$28	(	\$35	5	\$42	B	\$4F	O	\$5C	Yen	\$69	I	\$76	v		
\$29	)	\$36	6	\$43	C	\$50	P	\$5D	]	\$6A	J	\$77	w		
\$2A	*	\$37	7	\$44	D	\$51	Q	\$5E	^	\$6B	K	\$78	x		
\$2B	+	\$38	8	\$45	E	\$52	R	\$5F	~	\$6C	L	\$79	y		
\$2C	,	\$39	9	\$46	F	\$53	S	\$60	_	\$6D	M	\$7A	z		

**TABLE 2: MON12 Service Routine Jump Table**

ADDRESS			
ff10	JMP	MAIN	; warm start
ff13	JMP	BPCLR	; clear breakpoint table
ff16	JMP	RPRINT	; display user registers
ff19	JMP	HEXRIN	; convert ascii hex char to binary
ff1c	JMP	BUFFARG	; build hex argument from buffer
ff1f	JMP	TERMARG	; read hex argument from terminal
ff22	JMP	CHGBYT	; modify memory byte at address in x
ff25	JMP	CHGWORD	; modify memory word at address in x
ff28	JMP	READBUFF	; read character from buffer
ff2b	JMP	INCBUFF	; increment buffer pointer
ff2e	JMP	DECBUFF	; decrement buffer pointer
ff31	JMP	WSKIP	; find non-whitespace char in buffer
ff34	JMP	CHKABRT	; check for abort from terminal
ff37	JMP	UPCASE	; convert to upper case
ff3a	JMP	WCHK	; check for white space
ff3d	JMP	DCHK	; check for delimiter
ff40	JMP	ONSCIO	; initialize i/o device
ff43	JMP	INPUT	; low level input routine
ff46	JMP	OUTPUT	; low level output routine
ff49	JMP	OUTLHLF	; display top 4 bits as hex digit
ff4c	JMP	OUTRHLF	; display bottom 4 bits as hex digit
ff4f	JMP	OUTA	; output ascii character in A
ff52	JMP	OUT18YT	; display the hex value of byte at X
ff55	JMP	OUT18SP	; out1byt followed by space
ff58	JMP	OUT2BSP	; display 2 hex bytes (word) at x and a space
ff5b	JMP	OUTCRLF	; carriage return, line feed to terminal
ff5e	JMP	OUTSTRG	; display string at X (term with \$04)
ff61	JMP	OUTSTRG0	; outstrg with no initial carr ret
ff64	JMP	INCHAR	; wait for and input a char from term
ff67	JMP	VECINIT	; initialize RAM vector table

CML12SDP256

01/30/04

TABLE 3: MON12 Interrupt Table

MON12 Ram Interrupt Vector	HCS12 Interrupt Vector Address	MON12 TRAP code	Vector Source
3F8C	FF8C	02	PWME
3F8E	FF8E	04	PTPI
3F90	FF90	06	C4TX
3F92	FF92	08	C4RX
3F94	FF94	0A	C4ERR
3F96	FF96	0C	C4WU
3F98	FF98	0E	C3TX
3F9A	FF9A	10	C3RX
3F9C	FF9C	12	C3ERR
3F9E	FF9E	14	C3WU
3FA0	FFA0	16	C2TX
3FA2	FFA2	18	C2RX
3FA4	FFA4	1A	C2ERR
3FA6	FFA6	1C	C2WU
3FA8	FFA8	1E	C1TX
3FAA	FFAA	20	C1RX
3FAC	FFAC	22	C1ERR
3FAE	FFAE	24	C1WU
3FB0	FFB0	26	C0TX
3FB2	FFB2	28	C0RX
3FB4	FFB4	2A	C0ERR
3FB6	FFB6	2C	C0WU
3FB8	FFB8	2E	FEPRG
3FBA	FFBA	30	EEPRG
3FBC	FFBC	32	SPI2
3FBE	FFBE	34	SPI1
3FC0	FFC0	36	I2C
3FC2	FFC2	38	BDLC
3FC4	FFC4	3A	CRGC
3FC6	FFC6	3C	CRGL
3FC8	FFC8	3E	PACBO
3FCA	FFCA	40	MCNT
3FCC	FFCC	42	PTI
3FCE	FFCE	44	PTJI
3FD0	FFD0	46	ADC1
3FD2	FFD2	48	ADC0
3FD4	FFD4	4A	SCI1
3FD6	FFD6	4C	SCI0
3FD8	FFD8	4E	SPI0
3FDA	FFDA	50	PACAI
3FDC	FFDC	52	PACAO
3FDE	FFDE	54	TOF
3FE0	FFE0	56	TC7
3FE2	FFE2	58	TC6
3FE4	FFE4	5A	TC5
3FE6	FFE6	5C	TC4
3FE8	FFE8	5E	TC3
3FEA	FFEA	60	TC2
3FEC	FFEC	62	TC1
3FEE	FFEE	64	TC0
3FF0	FFF0	66	RTI
3FF2	FFF2	68	IRQ
3FF4	FFF4	6A	XIRQ
3FF6	FFF6	6C	SWI
3FF8	FFF8	6E	TRAP
3FFA	FFFA	70	COP
3FFC	FFFC	72	CLM
	FFFE		RESET

## CML-9S12DP512

Description: Low cost development system for the MC9S12DP512



Product Image:

[Get original file \(61KB\)](#)

**Product Summary:** The CML-912SDP512 is a low cost development system for the Motorola MC9S12DP512 Microcontroller. The board provides operation in Single-Chip Mode with the Expanded Wide Bus available for expansion and development memory access. The system is supplied with Monitor / Debugger installed with programming support utilities. Features provide for easy selection of operation mode, flash programming, BDM operation, keypad and LCD module connections, and prototyping. All required power supplies and support software is included to complete and program an application.

**Features:** • MC9S12DP512 Features:

Upward code compatible w/ 68HC11

4K Bytes EEPROM

512K Byte Flash EEPROM

14K Byte SRAM

2 Enhanced SCI Ports

3 SPI Port (Synchronous Serial)

5 CAN 2.0 A or B Interface

Two 8 Channel 10 Bit Analog Converters

Background Debug Port

Enhanced 16 bit Timer w/ 8 channels

of capture or compare

16 Bit Pulse Accumulator

8 PWM Channels

Two 8 bit Key Wake-up ports



PLL Clock Oscillator Support

RTC and COP features

Up to 91 I/O

- 4Mhz reference oscillator for up to 24MHz operation.
- External Memory: 256K Bytes (128K x 16) SRAM
- COM1 Port HC12 SCI0 w/ RS232 and DB9S connector
- COM2 Port HC12 SCI1 w/ RS232 and 3 pin header
- INDICATORS Power and RESET.
- BUS-PORT 40 Pin Socket Header
- MCU I/O PORT - 60 pin Socket Header
- Analog Port 20 pin Socket Header
- CAN PORT CAN 0 I/O with 1M Baud Transceiver
- LCD Module and Keypad Ports
- Solderless Prototype Area and Connections
- Easy Power Connection and Tap points
- Back Ground Debug (BDM) Port 6 Pin standard

Specifications: • 7 to 25VDC input to 5V Power Supply

- Operating Power: 60ma @ 5V


Package Contents: The Axiom development system provides for low cost software debugging with the use of a Debug Monitor installed in the internal or external memory. Operation allows the user to locate code in the On-Board RAM, set Break Points, Trace, and display or modify registers or memory. After code is operational the user may relocate the code and program the MC9S12DP512 internal Flash for dedicated operation of new software. No additional hardware or software is required. Board is compatible with standard HC12 BDM pods and software compilers that provide an integrated debug interface.

## Appendix B: Motor Driver Datasheet

# SLA7024M, SLA7026M, AND SMA7029M

Data Sheet  
28201

## HIGH-CURRENT PWM, UNIPOLAR STEPPER MOTOR CONTROLLER/DRIVERS



### ABSOLUTE MAXIMUM RATINGS at $T_A = +25^\circ\text{C}$

Load Supply Voltage, $V_{BB}$	46 V
FET Output Voltage, $V_{DS}$	100 V
Control Supply Voltage, $V_{CC}$	46 V
Peak Output Current, $I_{OUTM}$ ( $t_p \leq 100 \mu\text{s}$ )	3.0 A
SLA7024M	3.0 A
SLA7026M	5.0 A
SMA7029M	3.0 A
Continuous Output Current, $I_{OUT}$	
SLA7024M	1.5 A
SLA7026M	3.0 A
SMA7029M	1.5 A
Input Voltage Range, $V_{IN}$	-0.3 V to 7.0 V
Reference Voltage, $V_{REF}$	2.0 V
Package Power Dissipation, $P_D$	See Graph
Junction Temperature, $T_J$	+150°C
Operating Temperature Range, $T_A$	-20°C to +85°C
Storage Temperature Range, $T_{STG}$	-40°C to +150°C

The SLA7024M, SLA7026M, and SMA7029M are designed for high-efficiency and high-performance operation of 2-phase, unipolar stepper motors. An automated, innovative packaging technology combined with power FETs and monolithic logic/control circuitry advances power multi-chip modules (PMCMs™) toward the complete integration of motion control. Highly automated manufacturing techniques provide low-cost and exceptionally reliable PMCMs suitable for controlling and directly driving a broad range of 2-phase, unipolar stepper motors. The three stepper motor multi-chip modules differ primarily in output current ratings (1.5 A or 3.0 A) and package style.

All three PMCMs are rated for an absolute maximum limit of 46 V and utilize advanced NMOS FETs for the high-current, high-voltage driver outputs. The avalanche-rated ( $\geq 100$  V) FETs provide excellent ON resistance, improved body diodes, and very-fast switching. The multi-chip ratings and performance afford significant benefits and advantages for stepper drives when compared to the higher dissipation and slower switching speeds associated with bipolar transistors. Normally, heat sinks are not required for the SLA7024M or SMA7029M. The SLA7026M, in demanding, higher-current systems designs, necessitates suitable heat transfer methods for reliable operation.

Complete applications information is given on the following pages. PWM current is regulated by appropriately choosing current-sensing resistors, a voltage reference, a voltage divider, and RC timing networks. The RC components limit the OFF interval and control current decay. Inputs are compatible with 5 V logic and microprocessors.

### BENEFITS AND FEATURES


- Cost-Effective, Multi-Chip Solution
- 'Turn-Key' Motion-Control Module
- Motor Operation to 3 A and 46 V
- 3rd Generation High-Voltage FETs
- 100 V, Avalanche-Rated NMOS
- Low  $r_{DS(on)}$  NMOS Outputs
- Advanced, Improved Body Diodes
- Single-Supply Motor/Module Operation
- Half- or Full-Step Unipolar Drive
- High-Efficiency, High-Speed PWM
- Dual PWM Current Control (2-Phase)
- Programmable PWM Current Control
- Low Component Count PWM Drive
- Low Internal Power Dissipation
- Heat Sinking (Normally) Unnecessary
- Electrically Isolated Power Tab
- Logic/IC- and  $\mu\text{P}$ -Compatible Inputs
- Machine-Insertable Package

Always order by complete part number:

Part Number	Package	Output Current
SLA7024M	18-Lead Power-Tab SIP	1.5 A
SLA7026M	18-Lead Power-Tab SIP	3.0 A
SMA7029M	15-Lead SIP	1.5 A


## SLA7024M, SLA7026M, AND SMA7029M HIGH-CURRENT PWM, UNIPOLAR STEPPER MOTOR CONTROLLER/DRIVERS

### SLA7024M and SLA7026M FUNCTIONAL BLOCK DIAGRAM



Note that channels A and B are electrically isolated.

### SMA7029M FUNCTIONAL BLOCK DIAGRAM



Note that except for the control supply, channels A and B are electrically isolated.

SanKen

Allegro  
MicroSystems, Inc.


Allegro  
MicroSystems, Inc.

115 Northeast Cutoff, Box 15036  
Worcester, Massachusetts 01615-0036 (508) 853-5000  
Copyright © 1994 Allegro Microsystems, Inc.


SanKen

**SLA7024M, SLA7026M, AND SMA7029M**  
**HIGH-CURRENT PWM,**  
**UNIPOLAR STEPPER MOTOR**  
**CONTROLLER/DRIVERS**

**ALLOWABLE PACKAGE**  
**POWER DISSIPATION**



**SLA7024M and SLA7026M**




**ELECTRICAL CHARACTERISTICS at  $T_A = +25^\circ\text{C}$**

Characteristic	Symbol	Test Conditions	Limits		
			Min	Typ	Max
FET Leakage Current	$I_{DSS}$	$V_{DS} = 100\text{ V}, V_{CC} = 44\text{ V}$			4.0
FET ON Voltage	$V_{DS(on)}$	(SLA7024M & SMA7029M) $V_{CC} = 14\text{ V}, I_{OUT} = 1\text{ A}$			600
		(SLA7026M) $V_{CC} = 14\text{ V}, I_{OUT} = 3\text{ A}$			850
FET ON Resistance	$r_{DS(on)}$	(SLA7024M & SMA7029M) $V_{CC} = 14\text{ V}, I_{OUT} = 1\text{ A}$			600
		(SLA7026M) $V_{CC} = 14\text{ V}, I_{OUT} = 3\text{ A}$			285
Body Diode	$V_{SD}$	(SLA7024M & SMA7029M) $I_{OUT} = 1\text{ A}$		0.9	1.5
Forward Voltage		(SLA7026M) $I_{OUT} = 3\text{ A}$		0.9	1.6
Control Supply Voltage	$V_{CC}$	Operating	10	24	44
Control Supply Current	$I_{CC}$	$V_{CC} = 44\text{ V}$		10	15
Input Current	$I_{IN(H)}$	$V_{CC} = 44\text{ V}, V_{IN} = 2.4\text{ V}$			40
		$V_{IN} = 0.4\text{ V}$			-800
Input Voltage	$V_{IN(H)}$		2.0		
				0.8	

NOTE: Negative current is defined as coming out of (sourcing) the specified device pin.

**SLA7024M, SLA7026M, AND SMA7029M**  
**HIGH-CURRENT PWM,**  
**UNIPOLAR STEPPER MOTOR**  
**CONTROLLER/DRIVERS**

**TYPICAL STEPPER MOTOR APPLICATIONS**  
**(Half of Each Device Shown)**  
**SLA7024M and SLA7026M**



**TRUTH TABLES**  
**(Device Types as Designated)**

**WAVE DRIVE (FULL STEP)**  
**for SLA7024M and SLA7026M**

Sequence	0	1	2	3	0
Input A	H	L	L	L	H
Input A'	L	L	H	L	L
Input B	L	H	L	L	L
Input B'	L	L	L	H	L
Output ON	A	B	A	B	A

**2-PHASE (FULL STEP) OPERATION**  
**for SLA7024M and SLA7026M**

Sequence	0	1	2	3	0
Input A	H	L	L	H	H
Input A'	L	H	H	L	L
Input B	H	H	L	L	H
Input B'	L	L	H	H	L
Outputs ON	AB	A'B	AB	A'B	AB

**HALF-STEP OPERATION (2-1-2 SEQUENCE)**  
**for SLA7024M, SLA7026M, and SMA7029M**

Sequence	0	1	2	3	4	5	6	7	0
Input A	H	H	L	L	L	L	L	H	H
Input A' or $t_{AB}^*$	L	L	L	H	H	H	L	L	L
Input B	L	H	H	H	L	L	L	L	L
Input B' or $t_{BA}^*$	L	L	L	L	L	H	H	H	L
Output(s) ON	A	AB	B	A'B	A	B'	A'B	A	

\*Logic signals to external open-collector inverter connected to  $t_{AB}$  and  $t_{BA}$ .




115 Northeast Cutoff, Box 15036  
 Worcester, Massachusetts 01615-0036 (508) 853-5000



**SLA7024M, SLA7026M, AND SMA7029M**  
**HIGH-CURRENT PWM,**  
**UNIPOLAR STEPPER MOTOR**  
**CONTROLLER/DRIVERS**

**TYPICAL STEPPER MOTOR APPLICATIONS**  
 (Half of Device Shown)  
**SMA7029M**



**TRUTH TABLES**  
 (SMA7029M Only)

**WAVE DRIVE (FULL STEP) for SMA7029M**

Sequence	0	1	2	3	0
Input A	H	L	L	L	H
Input toA*	L	L	H	L	L
Input B	L	H	L	L	L
Input toB*	L	L	L	H	L
Output ON	A	B	A	B	A

\*Logic signals to external open-collector inverter connected to  $t_{A*}$  and  $t_{B*}$ .

**2-PHASE (FULL STEP) OPERATION**  
 for SMA7029M

Sequence	0	1	2	3	0
Input A	H	H	L	L	H
Input B	L	H	H	L	L
Outputs ON	A B	AB	A B	AB	A B

**SLA7024M, SLA7026M, AND SMA7029M**  
**HIGH-CURRENT PWM,**  
**UNIPOLAR STEPPER MOTOR**  
**CONTROLLER/DRIVERS**

**APPLICATIONS INFORMATION**

**REGULATING THE PWM OUTPUT CURRENT**

The output current (and motor coil current) waveform is illustrated in Figure 1. Setting the PWM current trip point requires various external components:

$V_b$  = Reference supply (typically 5 V)

$R_1, R_2$  = Voltage-divider resistors in the reference supply circuit

$R_s$  = Current sensing resistor(s)

NOTE: The maximum allowable  $V_{REF}$  input voltage is 2.0 V. The voltage-divider must be selected accordingly.


**Normal PWM (Full-Current/Running) Mode**

$I_{OUT}$  is set to meet the specified running current for the motor (Figure 2) and is determined by:

$$I_{OUT} = \frac{V_{REF}}{R_s} \quad (1)$$


or, if  $V_{REF}$  is not known

$$I_{OUT} = \frac{R_2}{R_1 + R_2} \cdot \frac{V_b}{R_s} \quad (2)$$



(Fig. 1C-001)

**FIGURE 1. PHASE A COIL CURRENT WAVEFORM**



(Fig. 2C-001)

**FIGURE 2. PWM CONTROL (RUN MODE)**




115 Northeast Cutoff, Box 15036  
 Worcester, Massachusetts 01615-0036 (508) 853-5000



**SLA7024M, SLA7026M, AND SMA7029M**  
**HIGH-CURRENT PWM,**  
**UNIPOLAR STEPPER MOTOR**  
**CONTROLLER/DRIVERS**

For given values of  $R_1$ ,  $R_2$ , and  $V_b$  ( $V_{REF} = 0.82 \text{ V}$ ), Figure 3 illustrates output current as a function of current-sensing resistance ( $R_s$ ).



**FIGURE 3. CURRENT-SENSING RESISTANCE**


**Reduced/Holding Current Mode**

Additional circuitry (Figure 4) enables reducing motor current. The external transistor changes the voltage-divider ratio,  $V_{REF}$ , and reduces the output current.  $I_{HOLD}$  is determined by resistors  $R_2$  and  $R_X$  in parallel:

$$I_{HOLD} = \frac{R_2 R_X}{R_1 R_2 + R_1 R_X + R_2 R_X} \cdot \frac{V_b}{R_s} \quad (3)$$

$$\text{or } I_{HOLD} = \frac{R_2 \tilde{R}}{R_1 + R_2 \tilde{R}} \cdot \frac{V_b}{R_s} \quad (4)$$


where  $\tilde{R}$  is the equivalent value of  $R_2$  and  $R_X$  in parallel.




**FIGURE 4. HOLD CURRENT MODE**

**SLA7024M, SLA7026M, AND SMA7029M**  
**HIGH-CURRENT PWM,**  
**UNIPOLAR STEPPER MOTOR**  
**CONTROLLER/DRIVERS**

For given values of  $R_1$ ,  $R_2$ , and  $V_b$  ( $V_{REF} = 0.82 \text{ V}$ ), Figures 5A and 5B illustrate output holding current as a function of  $R_X$  for two values of current-sensing resistance ( $R_s$ ).



**FIGURE 5A. HOLD-CURRENT RESISTANCE (SLA7024M and SMA7029M)**



**FIGURE 5B. HOLD-CURRENT RESISTANCE (SLA7026M)**

**NOTE:** Holding current determines holding torque, which is normally greater than running torque. Consult motor manufacturer for recommended safe holding current and motor winding temperature limits in "standstill" or "detent" mode.

The MOSFET outputs create ringing noise with PWM, but the RC filter precludes malfunctions. The comparator operation is affected by  $R_s$  and  $C_s$  and, thus, current overshoot is influenced by component values. Empirical adjustment to "fine-tune" the current limit is likely.



**SLA7024M, SLA7026M, AND SMA7029M  
HIGH-CURRENT PWM,  
UNIPOLAR STEPPER MOTOR  
CONTROLLER/DRIVERS**


**DETERMINING THE MOTOR PWM FREQUENCY**

The modules function asynchronously, with PWM OFF time fixed by  $R_3$  and  $C_1$  at input  $t_{off}$ . The OFF time can be calculated as:

$$t_{OFF} = -R_3 \cdot C_1 \cdot \log_n \left(1 - \frac{2}{V_o}\right) \quad (5)$$

Recommended circuit constants and  $t_{OFF}$  are:

$$\begin{aligned} V_o &= 5 \text{ V} \\ R_3 &= 47 \text{ k}\Omega \\ C_1 &= 470 \text{ pF} \\ t_{OFF} &= 12 \text{ }\mu\text{s} \end{aligned}$$



**FIGURE 7.  
PWM FREQUENCY vs MOTOR RESISTANCE**

**POWER DISSIPATION CALCULATIONS**

Excepting high-current applications utilizing the SLA7026M above approximately 2.0 A at +65°C (with 2-phase operation), the need for heat sinks is rare. The basic constituents of conduction losses (internal power dissipation) include:

- (a) FET output power dissipation ( $I_{OUT}^2 \cdot r_{DS(on)}$  or  $I_{OUT} \cdot V_{DS(on)}$ ),
- (b) FET body diode power dissipation ( $V_{SD} \cdot I_{OUT}$ ), and
- (c) control circuit power dissipation ( $V_{CC} \cdot I_{CC}$ ).

Device conduction losses are calculated based on the operating mode (wave drive, half-step, or 2-phase). Assuming a 50% output duty cycle:

$$\begin{aligned} \text{Wave Drive} &= 0.5 (I_{OUT}^2 \cdot r_{DS(on)}) + 0.5 (V_{SD} \cdot I_{OUT}) + (V_{CC} \cdot 15 \text{ mA}) \\ \text{Half-Step} &= 0.75 (I_{OUT}^2 \cdot r_{DS(on)}) + 0.75 (V_{SD} \cdot I_{OUT}) + (V_{CC} \cdot 15 \text{ mA}) \\ \text{2-Phase} &= (I_{OUT}^2 \cdot r_{DS(on)}) + (V_{SD} \cdot I_{OUT}) + (V_{CC} \cdot 15 \text{ mA}) \end{aligned}$$

**SLA7024M, SLA7026M, AND SMA7029M  
HIGH-CURRENT PWM,  
UNIPOLAR STEPPER MOTOR  
CONTROLLER/DRIVERS**

**PACKAGE RATINGS/DERATING FACTORS**

Thermal ratings/deratings for the multi-chip module packages vary slightly. Normally, the SLA7024M and SMA7029M do not need heat sinking when operated within maximum specified output current ( $\leq 1.0$  A with 2-phase drive) unless the design ambient temperature also exceeds +60°C. Thermal calculations must also consider the temperature effects on the output FET ON resistance. The applicable thermal ratings for the PMCM packages are:

**SLA7024M and SLA7026M 18-Lead Power-Tab SIP**


$R_{\theta JA} = 28^\circ\text{C/W}$  (no heat sink) or 4.5 W at +25°C and a derating factor of -36 mW/°C for operation above +25°C.  $R_{\theta JC} = 5^\circ\text{C/W}$ .

**SMA7029M 15-Lead SIP**

$R_{\theta JA} = 31^\circ\text{C/W}$  (no heat sink) or 4.0 W at +25°C and a derating factor of -32 mW/°C for operation above +25°C.  $R_{\theta JC} = 6^\circ\text{C/W}$ .

**TEMPERATURE EFFECTS ON FET  $r_{DS(on)}$**

Analyzing safe, reliable operation includes a concern for the relationship of NMOS ON resistance to junction temperature. Device package power calculations must include the increase in ON resistance (producing higher output ON voltages) caused by higher operating junction temperatures. Figure 8 provides a normalized ON resistance curve, and all thermal calculations should consider increases from the given +25°C limits, which may be caused by internal heating during normal operation.



**FIGURE 8. NORMALIZED ON RESISTANCE  
vs TEMPERATURE**




115 Northeast Cut-off, Box 15036  
Worcester, Massachusetts 01615-0036 (508) 853-5000




**SLA7024M, SLA7026M, AND SMA7029M**  
**HIGH-CURRENT PWM,**  
**UNIPOLAR STEPPER MOTOR**  
**CONTROLLER/DRIVERS**

**SLA7024M and SLA7026M**  
Dimensions in Inches  
(for reference only)




Dimensions in Millimeters  
(controlling dimensions)




- NOTES: 1. Exact body and lead configuration at vendor's option within limits shown.  
2. Recommended mounting hardware torque: 4.34 – 5.79 lbf·ft (6 – 8 kgf·cm or 0.588 – 0.784 Nm).  
3. The hatched area is exposed (electrically isolated) heatspreader.  
4. Recommend use of metal-oxide-filled, alkyl-degenerated oil base, silicone grease (Dow Corning 340 or equivalent).

**SLA7024M, SLA7026M, AND SMA7029M**  
**HIGH-CURRENT PWM,**  
**UNIPOLAR STEPPER MOTOR**  
**CONTROLLER/DRIVERS**

**SMA7029M**  
Dimensions in Inches  
(for reference only)



Dimensions in Millimeters  
(controlling dimensions)



NOTE: Exact body and lead configuration at vendor's option within limits shown.

The products described here are manufactured in Japan by Sanken Electric Co., Ltd. for sale by Allegro MicroSystems, Inc. Sanken Electric Co., Ltd. and Allegro MicroSystems, Inc. reserve the right to make, from time to time, such departures from the detail specifications as may be required to permit improvements in the design of their products. The information included herein is believed to be accurate and reliable. However, Sanken Electric Co., Ltd. and Allegro MicroSystems, Inc. assume no responsibility for its use, nor for any infringements of patents or other rights of third parties which may result from its use.



115 Northeast Cutoff, Box 15036  
Worcester, Massachusetts 01615-0036 (508) 853-5000






## Appendix C: RFID Datasheet

## RFID Reader Module (#28140)

RFID 54 mm x 85 mm Rectangle Tag (#28141)

RFID 50 mm Round Tag (#28142)



### Introduction

Designed in cooperation with Grand Idea Studio (<http://www.grandideastudio.com/>), the Parallax Radio Frequency Identification (RFID) Reader Module is the first low-cost solution to read passive RFID transponder tags up to 1 3/4" - 3" inches away depending on the tag (see list below). The RFID Reader Module can be used in a wide variety of hobbyist and commercial applications, including access control, automatic identification, robotics navigation, inventory tracking, payment systems, and car immobilization.

- Fully-integrated, low-cost method of reading passive RFID transponder tags
- 1-wire, 2400 baud Serial TTL interface to PC, BASIC Stamp® and other processors
- Requires single +5VDC supply
- Bi-color LED for visual indication of activity
- 0.100" pin spacing for easy prototyping and integration


The Parallax RFID Reader Module works exclusively with the EM Microelectronics-Marin SA EM4100-family of passive read-only transponder tags. A variety of different tag types and styles exist with the most popular made available from Parallax. Each transponder tag contains a unique identifier (one of 2<sup>40</sup>, or 1,099,511,627,776, possible combinations) that is read by the RFID Reader Module and transmitted to the host via a simple serial interface.

### Electronic Connections

The Parallax RFID Reader Module can be integrated into any design using only four connections (VCC, /ENABLE, SOUT, GND). Use the following circuit for connecting the Parallax RFID Reader Module to the BASIC Stamp microcontroller:

Pin	Pin Name	Type	Function
1	VCC	P	System power, +5V DC input.
2	/ENABLE	I	Module enable pin. Active LOW digital input. Bring this pin LOW to enable the RFID reader and activate the antenna.
3	SOUT	O	Serial Out. TTL-level interface, 2400bps, 8 data bits, no parity, 1 stop bit.
4	GND	G	System ground. Connect to power supply's ground (GND) terminal.

Note: Type: I = Input, O = Output, P = Power, G = Ground



## Communication Protocol

Implementation and usage of the RFID Reader Module is straightforward. BASIC Stamp 1, 2, and SX28AC/DP code examples (SX/B) are included at the end of this documentation.

The RFID Reader Module is controlled with a single TTL-level active-low /ENABLE pin. When the /ENABLE pin is pulled LOW, the module will enter its active state and enable the antenna to interrogate for tags. The current consumption of the module will increase dramatically when the module is active.

A visual indication of the state of the RFID Reader Module is given with the on-board LED. When the module is successfully powered-up and is in an idle state, the LED will be GREEN. When the module is in an active state and the antenna is transmitting, the LED will be RED.

The face of the RFID tag should be held parallel to the front or back face of the antenna (where the majority of RF energy is focused). If the tag is held sideways (perpendicular to the antenna) you'll either get no reading or a poor reading. Only one transponder tag should be held up to the antenna at any time. The use of multiple tags at one time will cause tag collisions and confuse the reader. The two tags available in the Parallax store have a read distance of approximately 3 inches. Actual distance may vary slightly depending on the size of the transponder tag and environmental conditions of the application.

When a valid RFID transponder tag is placed within range of the activated reader, the unique ID will be transmitted as a 12-byte ASCII string via the TTL-level SCOUT (Serial Output) pin in the following format:

MSB										LSB	
Start Byte (0xAA)	Unique ID Digit 1	Unique ID Digit 2	Unique ID Digit 3	Unique ID Digit 4	Unique ID Digit 5	Unique ID Digit 6	Unique ID Digit 7	Unique ID Digit 8	Unique ID Digit 9	Unique ID Digit 10	Stop Byte (0x00)

The start byte and stop byte are used to easily identify that a correct string has been received from the reader (they correspond to a line feed and carriage return characters, respectively). The middle ten bytes are the actual tag's unique ID.

All communication is 8 data bits, no parity, 1 stop bit, non-inverted, least significant bit first (LSB). The baud rate is configured for 2400bps, a standard communications speed supported by most any microprocessor or PC, and cannot be changed. The Parallax RFID Reader Module initiates all communication. The Parallax RFID Reader Module can connect directly to any TTL-compatible UART or to an RS232-compatible interface by using an external level shifter.

## Absolute Maximum Ratings and Electrical Characteristics

Condition	Value
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +125°C
Supply Voltage ( $V_{CC}$ )	+4.5V to +5.5V
Ground Voltage ( $V_{SS}$ )	0V
Voltage on any pin with respect to $V_{SS}$	-0.3V to +7.0V

Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at those or any other conditions above those indicated in the operation listings of this specification is not implied. Exposure to maximum rating conditions for extended periods may affect device reliability.

## DC Characteristics


At  $V_{CC} = +5.0V$  and  $T_A = 25^\circ C$  unless otherwise noted

Parameter	Symbol	Test Conditions	Specification			Unit
			Min.	Typ.	Max.	
Supply Voltage	$V_{CC}$	—	4.5	5.0	5.5	V
Supply Current, Idle	$I_{DD, I}$	—	—	10	—	mA
Supply Current, Active	$I_{DD, A}$	—	—	90	—	mA
Input LOW voltage	$V_{IL}$	$+4.5V \leq V_{CC} \leq +5.5V$	—	—	0.8	V
Input HIGH voltage	$V_{IH}$	$+4.5V \leq V_{CC} \leq +5.5V$	2.0	—	—	V
Output LOW voltage	$V_{OL}$	$V_{CC} = +4.5V$	—	—	0.6	V
Output HIGH voltage	$V_{OH}$	$V_{CC} = +4.5V$	$V_{CC} - 0.7$	—	—	V

## RFID Tags Available From Parallax

Parallax provides two passive RFID tags from our on-line store. We're stocking the tags because many suppliers have high minimums, yet many of our customers may only want a few tags for their basic experimentation.

- 54 mm x 85 mm Rectangle Tag (#28141)
- 50 mm Round Tag (#28142)



Actual tag dimensions may vary. Contact Parallax for specific information.

### Optional Tag Information

Even though Parallax only carries a Round Tag and a Rectangle Tag the following values were obtained from different tags available in the market.

ISO Card:	6.3cm (2.5") +/- 10%
World Tag 50mm:	6.8cm (2.7") +/- 10%
World Tag 30mm:	5.3cm (2.1") +/- 10%
Bobsleigh Keyfob:	5.3cm (2.1") +/- 10%
Tear shape:	4.0cm (1.6") +/- 10%
Wristband:	4.0cm (1.6") +/- 10%

### RFID Technology Overview

Material in this section is based on information provided by the RFID Journal ([www.rfidjournal.com](http://www.rfidjournal.com)).

Radio Frequency Identification (RFID) is a generic term for non-contacting technologies that use radio waves to automatically identify people or objects. There are several methods of identification, but the most common is to store a unique serial number that identifies a person or object on a microchip that is attached to an antenna. The combined antenna and microchip are called an "RFID transponder" or "RFID tag" and work in combination with an "RFID reader" (sometimes called an "RFID interrogator").

An RFID system consists of a reader and one or more tags. The reader's antenna is used to transmit radio frequency (RF) energy. Depending on the tag type, the energy is "harvested" by the tag's antenna and used to power up the internal circuitry of the tag. The tag will then modulate the electromagnetic waves generated by the reader in order to transmit its data back to the reader. The reader receives the modulated waves and converts them into digital data. In the case of the Parallax RFID Reader Module, correctly received digital data is sent serially through the SCOUT pin.

There are two major types of tag technologies. "Passive tags" are tags that do not contain their own power source or transmitter. When radio waves from the reader reach the chip's antenna, the energy is converted by the antenna into electricity that can power up the microchip in the tag (known as "parasitic power"). The tag is then able to send back any information stored on the tag by reflecting the electromagnetic waves as described above. "Active tags" have their own power source and transmitter. The power source, usually a battery, is used to run the microchip's circuitry and to broadcast a signal to a reader. Due to the fact that passive tags do not have their own transmitter and must reflect their signal to the reader, the reading distance is much shorter than with active tags. However, active tags are typically larger, more expensive, and require occasional service. The RFID Reader Module is designed specifically for low-frequency (170 kHz) passive tags.

Frequency refers to the size of the radio waves used to communicate between the RFID system components. Just as you tune your radio to different frequencies in order to hear different radio stations, RFID tags and readers have to be tuned to the same frequency in order to communicate effectively. RFID systems typically use one of the following frequency ranges: low frequency (or LF, around 170 kHz), high frequency (or HF, around 13.56 MHz), ultra-high frequency (or UHF, around 868 and 928 MHz), or microwave (around 2.45 and 5.8 GHz). It is generally safe to assume that a higher frequency equates to a faster data transfer rate and longer read ranges, but also more sensitivity to environmental factors such as liquid and metal that can interfere with radio waves.

There really is no such thing as a "typical" RFID tag. The read range of a tag ultimately depends on many factors: the frequency of RFID system operation, the power of the reader, and interference from other RF devices. Balancing a number of engineering trade-offs (antenna size v. reading distance v. power v.

manufacturing cost), the Parallax RFID Reader Module's antenna was designed with a specific inductance and "Q" factor for 170kHz RFID operation at a tag read distance of up to 1 3/4" - 3" inches.

### Example Code

The following code examples read tags from a RFID Reader Module and compare the values to known tags (stored in an EEPROM table).

```

=====
'
' File..... RFID.BS1
' Purpose.... RFID Tag Reader / Simple Security System
' Author..... (c) Parallax, Inc. -- All Rights Reserved
' E-mail..... support@parallax.com
' Started.....
' Updated..... 07 FEB 2005
'
' {$STAMP BS1}
' {$PBASIC 1.0}
'
' -----
'
' -----[ Program Description ]-----
'
' Reads tags from a Parallax RFID reader and compares to known tags (stored
' in EEPROM table). If tag is found, the program will disable a lock.
'
' -----[ Revision History ]-----
'
' -----[ I/O Definitions ]-----
'
SYMBOL Enable      = 0          ' low = reader on
SYMBOL RX          = 1          ' serial from reader
SYMBOL Spkr        = 2          ' speaker output
SYMBOL Latch       = 3          ' lock/latch control
'
' -----[ Constants ]-----
'
SYMBOL LastTag     = 2          ' 3 tags; 0 to 2
'
' -----[ Variables ]-----
'
SYMBOL tag0        = B0          ' RFID byte0 buffer
SYMBOL tag1        = B1
SYMBOL tag2        = B2
SYMBOL tag3        = B3
SYMBOL tag4        = B4
SYMBOL tag5        = B5
SYMBOL tag6        = B6
SYMBOL tag7        = B7
SYMBOL tag8        = B8
SYMBOL tag9        = B9
'
SYMBOL tagNum      = B10         ' from EEPROM table
SYMBOL ptr         = B11         ' pointer to char in table
SYMBOL char        = B12         ' character from table

```

```

' -----[ EEPROM Data ]-----
Tags:
EEPROM ("0F0184F20B")      ' valid tags
EEPROM ("0F01D9D263")
EEPROM ("04129C1B43")
EEPROM ("0000000000")      ' space for other tags
EEPROM ("0000000000")

' -----[ Initialization ]-----

Reset:
HIGH Enable                ' turn of RFID reader
LOW Latch                  ' lock the door!

' -----[ Program Code ]-----

Main:
LOW Enable                 ' activate the reader
SERIN RX, T2400, ($0A)     ' wait for header
SERIN RX, T2400, tag0, tag1, tag2, tag3, tag4 ' get tag bytes
SERIN RX, T2400, tag5, tag6, tag7, tag8, tag9
HIGH Enable                ' deactivate reader

Check_List:
FOR tagNum = 0 TO LastTag ' scan through known tags
  pntr = tagNum * 10 + 0 : READ pntr, char ' read char from DB
  IF char <> tag0 THEN Bad_Char ' compare with tag data
  pntr = tagNum * 10 + 1 : READ pntr, char
  IF char <> tag1 THEN Bad_Char
  pntr = tagNum * 10 + 2 : READ pntr, char
  IF char <> tag2 THEN Bad_Char
  pntr = tagNum * 10 + 3 : READ pntr, char
  IF char <> tag3 THEN Bad_Char
  pntr = tagNum * 10 + 4 : READ pntr, char
  IF char <> tag4 THEN Bad_Char
  pntr = tagNum * 10 + 5 : READ pntr, char
  IF char <> tag5 THEN Bad_Char
  pntr = tagNum * 10 + 6 : READ pntr, char
  IF char <> tag6 THEN Bad_Char
  pntr = tagNum * 10 + 7 : READ pntr, char
  IF char <> tag7 THEN Bad_Char
  pntr = tagNum * 10 + 8 : READ pntr, char
  IF char <> tag8 THEN Bad_Char
  pntr = tagNum * 10 + 9 : READ pntr, char
  IF char <> tag9 THEN Bad_Char
  GOTO Tag_Found ' all match -- good tag
Bad_Char:
NEXT

Bad_Tag:
SOUND Spkr, (25, 80)      ' groan
PAUSE 1000
GOTO Main

Tag_Found:
DEBUG #tagNum, CR         ' for testing
HIGH Latch                ' remove latch
SOUND Spkr, (114, 165)    ' beep
LOW Latch                 ' restore latch

```

```

GOTO Main

END

' -----[ Program Description ]-----
' Reads tags from a Parallax RFID reader and compares to known tags (stored
' in EEPROM table). If tag is found, the program will disable a lock.

' -----[ Revision History ]-----

' -----[ I/O Definitions ]-----

Enable    PIN    0      ' low = reader on
RX         PIN    1      ' serial from reader
Spkr       PIN    2      ' speaker output
Latch      PIN    3      ' lock/latch control

' -----[ Constants ]-----

#SELECT $STAMP
#CASE BS2, BS2E, BS2PE
T1200     CON    813
T2400     CON    396
T4800     CON    188
T9600     CON    84
T19K2     CON    32
TMidi     CON    12
T38K4     CON    6
#CASE BS2SX, BS2P
T1200     CON    2063
T2400     CON    1021
T4800     CON    500
T9600     CON    240
T19K2     CON    110
TMidi     CON    60
T38K4     CON    45
#CASE BS2PX
T1200     CON    3313
T2400     CON    1646
T4800     CON    813
T9600     CON    396
T19K2     CON    188
TMidi     CON    108
T38K4     CON    84
#ENDSELECT

```

```

SevenBit    CON    $2000
Inverted     CON    $4000
Open        CON    $8000
Baud        CON    T2400

```

```

#SELECT $STAMP
#CASE BS2, BS2E
  TmAdj     CON    $100      ' x 1.0 (time adjust)
  FrAdj     CON    $100      ' x 1.0 (freq adjust)
#CASE BS2SX
  TmAdj     CON    $280      ' x 2.5
  FrAdj     CON    $066      ' x 0.4
#CASE BS2P
  TmAdj     CON    $3C5      ' x 3.77
  FrAdj     CON    $044      ' x 0.265
#CASE BS2PE
  TmAdj     CON    $100      ' x 1.0
  FrAdj     CON    $03A      ' x 0.665
#CASE BS2Px
  TmAdj     CON    $607      ' x 6.03
  FrAdj     CON    $2A       ' x 0.166
#ENDSELECT

```

```

LastTag     CON    3

```

```

#DEFINE No SPRAM = ($STAMP < BS2P)      ' does module have SPRAM?

```

```

' -----[ Variables ]-----

```

```

#IF No SPRAM #THEN
  buf       VAR    Byte(10)      ' RFID bytes buffer
#ELSE
  chkChar   VAR    Byte          ' character to test
#ENDIF

tagNum      VAR    Nib           ' from EEPROM table
idx         VAR    Byte          ' tag byte index
char        VAR    Byte          ' character from table

```

```

' -----[ EEPROM Data ]-----

```

```

Tag1       DATA    "0F0184F20B"      ' valid tags
Tag2       DATA    "0F01D9D263"
Tag3       DATA    "04129C1B43"

Name0      DATA    "Unauthorized", CR, 0
Name1      DATA    "George Johnston", CR, 0
Name2      DATA    "Dick Miller", CR, 0
Name3      DATA    "Mary Evans", CR, 0

```

```

' -----[ Initialization ]-----

```

```

Reset:
  HIGH Enable      ' turn of RFID reader
  LOW Latch        ' lock the door!

```

```

' -----[ Program Code ]-----

```

```

Main:
  LOW Enable      ' activate the reader
  #IF No SPRAM #THEN
    SERIN RX, T2400, [WAIT($0A), STR buf(10)] ' wait for hdr + ID
  #ELSE
    SERIN RX, T2400, [WAIT($0A), SPSTR 10]
  #ENDIF
  HIGH Enable     ' deactivate reader

```

```

Check List:
  FOR tagNum = 1 TO LastTag      ' scan through known tags
    FOR idx = 0 TO 9             ' scan bytes in tag
      READ (tagNum - 1 * 10 + idx), char ' get tag data from table
      #IF No SPRAM #THEN
        IF (char <> buf(idx)) THEN Bad_Char ' compare tag to table
      #ELSE
        GET idx, chkChar         ' read char from SPRAM
        IF (char <> chkChar) THEN Bad_Char ' compare to table
      #ENDIF
    NEXT
    GOTO Tag_Found              ' all bytes match!
  Bad_Char:
    NEXT                        ' try next tag

```

```

Bad_Tag:
  tagNum = 0
  GOSUB Show_Name               ' print message
  FREQUOT Spkr, 1000 * / TmAdj, 115 * / FrAdj ' groan
  PAUSE 1000
  GOTO Main

```

```

Tag_Found:
  GOSUB Show_Name              ' print name
  HIGH Latch                  ' remove latch
  FREQUOT Spkr, 2000 * / TmAdj, 880 * / FrAdj ' beep
  LOW Latch                   ' restore latch
  GOTO Main

```

```

' -----[ Subroutines ]-----

```

```

' Prints name associated with RFID tag

```

```

Show_Name:
  DEBUG DEC tagNum, ": "
  LOOKUP tagNum,
    [Name0, Name1, Name2, Name3], idx ' point to first character
  DO
    READ idx, char                    ' read character from name
    IF (char = 0) THEN EXIT           ' if 0, we're done
    DEBUG char                        ' otherwise print it
    idx = idx + 1                     ' point to next character
  LOOP
  RETURN

```

## Appendix D: Real Time Clock Chip Datasheet



Distributed by:  
**JAMECO**  
ELECTRONICS  
www.Jameco.com + 1-800-831-4242  
The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 133444



www.dalsemi.com

DS1286

Watchdog Timekeeper

## FEATURES

- Keeps track of hundredths of seconds, seconds, minutes, hours, days, date of the month, months, and years; valid leap year compensation up to 2100
- Watchdog timer restarts an out-of-control processor
- Alarm function schedules real time-related activities
- Embedded lithium energy cell maintains time, watchdog, user RAM, and alarm information
- Programmable interrupts and square wave outputs maintain 28-pin JEDEC footprint
- All registers are individually addressable via the address and data bus
- Accuracy is better than  $\pm 1$  minute/month at 25°C
- Greater than 10 years of timekeeping in the absence of  $V_{CC}$
- 50 bytes of user NV RAM

## PIN ASSIGNMENT

INTA	1	28	$V_{CC}$
NC	2	27	$\overline{WE}$
NC	3	26	INTB (INTB)
NC	4	25	NC
A5	5	24	NC
A4	6	23	SQW
A3	7	22	$\overline{OE}$
A2	8	21	NC
A1	9	20	$\overline{CE}$
A0	10	19	DQ7
DQ0	11	18	DQ6
DQ1	12	17	DQ5
DQ2	13	16	DQ4
GND	14	15	DQ3

28-Pin Encapsulated Package  
(720-Mil Flush)

## PIN DESCRIPTION

INTA	- Interrupt Output A (open drain)
INTB (INTB)	- Interrupt Output B (open drain)
A0-A5	- Address Inputs
DQ0-DQ7	- Data Input/Output
$\overline{CE}$	- Chip Enable
$\overline{OE}$	- Output Enable
$\overline{WE}$	- Write Enable
$V_{CC}$	- +5 Volts
GND	- Ground
NC	- No Connection
SQW	- Square Wave Output

## DESCRIPTION

The DS1286 Watchdog Timekeeper is a self-contained real time clock, alarm, watchdog timer, and interval timer in a 28-pin JEDEC DIP package. The DS1286 contains an embedded lithium energy source and a quartz crystal which eliminates the need for any external circuitry. Data contained within 64 eight-bit registers can be read or written in the same manner as byte-wide static RAM. Data is maintained in the Watchdog Timekeeper by intelligent control circuitry which detects the status of  $V_{CC}$  and write protects memory when  $V_{CC}$  is out of tolerance. The lithium energy source can maintain data and real time for over 10 years in the absence of  $V_{CC}$ . Watchdog Timekeeper information includes hundredths of seconds, seconds, minutes, hours, day, date, month, and year. The date at the end of the month is automatically



adjusted for months with less than 31 days, including correction for leap year. The Watchdog Timekeeper operates in either 24-hour or 12-hour format with an AM/PM indicator. The watchdog timer provides alarm windows and interval timing between 0.01 seconds and 99.99 seconds. The real time alarm provides for preset times of up to one week.

## OPERATION - READ REGISTERS

The DS1286 executes a read cycle whenever  $\overline{WE}$  (Write Enable) is inactive (High) and  $\overline{CE}$  (Chip Enable) and  $\overline{OE}$  (Output Enable) are active (Low). The unique address specified by the six address inputs (A0-A5) defines which of the 64 registers is to be accessed. Valid data will be available to the eight data output drivers within  $t_{ACC}$  (Access Time) after the last address input signal is stable, providing that  $\overline{CE}$  and  $\overline{OE}$  access times are also satisfied. If  $\overline{OE}$  and  $\overline{CE}$  access times are not satisfied, then data access must be measured from the latter occurring signal ( $\overline{CE}$  or  $\overline{OE}$ ) and the limiting parameter is either  $t_{CO}$  for  $\overline{CE}$  or  $t_{OS}$  for  $\overline{OE}$  rather than address access.

## OPERATION - WRITE REGISTERS

The DS1286 is in the write mode whenever the  $\overline{WE}$  (Write Enable) and  $\overline{CE}$  (Chip Enable) signals are in the active (Low) state after the address inputs are stable. The latter occurring falling edge of  $\overline{CE}$  or  $\overline{WE}$  will determine the start of the write cycle. The write cycle is terminated by the earlier rising edge of  $\overline{CE}$  or  $\overline{WE}$ . All address inputs must be kept valid throughout the write cycle.  $\overline{WE}$  must return to the high state for a minimum recovery state ( $t_{WR}$ ) before another cycle can be initiated. Data must be valid on the data bus with sufficient Data Set Up ( $t_{DS}$ ) and Data Hold Time ( $t_{DH}$ ) with respect to the earlier rising edge of  $\overline{CE}$  or  $\overline{WE}$ . The  $\overline{OE}$  control signal should be kept inactive (High) during write cycles to avoid bus contention. However, if the output bus has been enabled ( $\overline{CE}$  and  $\overline{OE}$  active), then  $\overline{WE}$  will disable the outputs in  $t_{ODW}$  from its falling edge.

## DATA RETENTION


The Watchdog Timekeeper provides full functional capability when  $V_{CC}$  is greater than 4.5 volts and write protects the register contents at 4.25 volts typical. Data is maintained in the absence of  $V_{CC}$  without any additional support circuitry. The DS1286 constantly monitors  $V_{CC}$ . Should the supply voltage decay, the Watchdog Timekeeper will automatically write protect itself and all inputs to the registers become "Don't Care." Both  $\overline{INTA}$  and  $\overline{INTB}$  (INTB) are open drain outputs. The two interrupts and the internal clock continue to run regardless of the level of  $V_{CC}$ . However, it is important to insure that the pull-up resistors used with the interrupt pins are never pulled up to a value which is greater than  $V_{CC} + 0.3V$ . As  $V_{CC}$  falls below approximately 3.0 volts, a power switching circuit turns on the lithium energy source to maintain the clock, and timer data functionality. It is also required to insure that during this time (battery backup mode), the voltage present at  $\overline{INTA}$  and  $\overline{INTB}$  (INTB) never exceeds 3.0V. At all times the current on each should not exceed +2.1 mA or -1.0 mA. However, if the active high mode is selected for  $\overline{INTB}$  (INTB), this pin will only go high in the presence of  $V_{CC}$ . During power-up, when  $V_{CC}$  rises above approximately 3.0 volts, the power switching circuit connects external  $V_{CC}$  and disconnects the internal lithium energy source. Normal operation can resume after  $V_{CC}$  exceeds 4.5 volts for a period of 150 ms.

## WATCHDOG TIMEKEEPER REGISTERS

The Watchdog Timekeeper has 64 registers which are 8 bits wide that contain all of the Timekeeping, Alarm, Watchdog, Control, and Data information. The Clock, Calendar, Alarm, and Watchdog registers are memory locations which contain external (user-accessible) and internal copies of the data. The external copies are independent of internal functions except that they are updated periodically by the simultaneous transfer of the incremented internal copy (see Figure 1). The Command Register bits are affected by both internal and external functions. This register will be discussed later. The 50 bytes of RAM registers can only be accessed from the external address and data bus. Registers 0, 1, 2, 4, 6, 8, 9, and A contain time of day and date information (see Figure 2). Time of Day information is stored in BCD. Registers 3, 5, and 7 contain the Time of Day Alarm information. Time of Day Alarm information is stored in BCD. Register B is the Command Register and information in this register is binary. Registers C and D are the Watchdog Alarm registers and information which is stored in these two registers is in BCD. Registers E through 3F are user bytes and can be used to contain data at the user's discretion.

BLOCK DIAGRAM Figure 1

DS1286



DS1286 WATCHDOG TIMEKEEPER REGISTERS Figure 2

DS1286

		ADDRESS	[BIT 7               ]								RANGE	[BIT 0]		
CLOCK, CALENDAR, TIME OF DAY ALARM REGISTERS	{	0	0.1 SECONDS				0.01 SECONDS				00-99			
		1	0	10 SECONDS				SECONDS				00-59		
		2	0	10 MINUTES				MINUTES				00-59		
		3	M	10 MIN ALARM				MIN ALARM				00-59		
		4	0	12/24	10	A/P		10 HR	HOURS				01-12+A/P 00-23	
		5	M	12/24	10	A/P		10 HR	HR ALARM				01-12+A/P 00-23	
		6	0	0	0	0	0	0	DAYS				01-07	
		7	M	0	0	0	0	0	DAY ALARM				01-07	
		8	0	0	10 DATE				DATE				01-31	
		9	EOSC	ESQW	0	10 MO				MONTHS				01-12
COMMAND REGISTERS	{	A	10 YEARS				YEARS				00-99			
		B	TE	IPSW	IBH	PU	WAM	TDM	WAF	TDF				
WATCHDOG ALARM REGISTERS	{	C	0.1 SECONDS				0.01 SECONDS				00-99			
		D	10 SECONDS				SECONDS				00-99			
(RETRIGGERABLE/ REPETITIVE COUNTDOWN ALARM)	{	E												
		3F												

## TIME OF DAY REGISTERS

Registers 0, 1, 2, 4, 6, 8, 9, and A contain Time of Day data in BCD. Ten bits within these eight registers are not used and will always read 0 regardless of how they are written. Bits 6 and 7 in the Months Register (9) are binary bits. When set to logic 0, EOSC (bit 7) enables the Real Time Clock oscillator. This bit is set to logic 1 as shipped from Dallas Semiconductor to prevent lithium energy consumption during storage and shipment. This bit will normally be turned on by the user during device initialization. However, the oscillator can be turned on and off as necessary by setting this bit to the appropriate level. Bit 6 of this same byte controls the Square Wave Output (Pin 23). When set to logic 0, the Square Wave Output pin will output a 1024 Hz Square Wave Signal. When set to logic 1 the Square Wave Output pin is in a high impedance state. Bit 6 of the Hours Register is defined as the 12- or 24- hour Select Bit. When set to logic 1, the 12-hour format is selected. In the 12-hour format, bit 5 is the AM/PM bit with logic 1 being PM. In the 24-hour mode, bit 5 is the second 10-hour bit (20-23 hours). The Time of Day registers are updated every .01 seconds from the real time clock, except when the TE bit (bit 7 of Register B) is set low or the clock oscillator is not running. The preferred method of synchronizing data access to and from the Watchdog Timekeeper is to access the Command Register by doing a write cycle to address location 0B and setting the TE bit (Transfer Enable ) to a logic 0. This will freeze the External Time of Day registers at the present recorded time, allowing access to occur without danger of simultaneous update. When the watch registers have been read or written, a second write cycle to location 0B, setting the TE bit to a logic 1, will put the Time of Day registers back to being updated every 0.01 second. No time is lost in the real time clock because the internal copy of the Time of Day register buffers is continually incremented while the external memory registers are frozen.

An alternate method of reading and writing the Time of Day registers is to ignore synchronization. However, any single read may give erroneous data as the real time clock may be in the process of updating the external memory registers as data is being read. The internal copies of seconds through years are incremented and Time of Day Alarm is checked during the period that hundreds of seconds read 99 and are transferred to the external register when hundredths of seconds roll from 99 to 00. A way of making sure data is valid is to do multiple reads and compare. Writing the registers can also produce erroneous results for the same reasons. A way of making sure that the write cycle has caused proper update is to do read verifies and re-execute the write cycle if data is not correct. While the possibility of erroneous results from reads and write cycles has been stated, it is worth noting that the probability of an incorrect result is kept to a minimum due to the redundant structure of the Watchdog Timekeeper.

## TIME OF DAY ALARM REGISTERS

Registers 3, 5, and 7 contain the Time of Day Alarm registers. Bits 3, 4, 5, and 6 of Register 7 will always read 0 regardless of how they are written. Bit 7 of Registers 3, 5, and 7 are mask bits (Figure 3). When all of the mask bits are logic 0, a Time of Day Alarm will only occur when Registers 2, 4, and 6 match the values stored in Registers 3, 5, and 7. An alarm will be generated every day when bit 7 of Register 7 is set to a logic 1. Similarly, an alarm is generated every hour when bit 7 of Registers 7 and 5 is set to a logic 1. When bit 7 of Registers 7, 5, and 3 is set to a logic 1, an alarm will occur every minute when Register 1 (seconds) rolls from 59 to 00.

Time of Day Alarm registers are written and read in the same format as the Time of Day registers. The Time of Day Alarm Flag and Interrupt is always cleared when Alarm registers are read or written.

## WATCHDOG ALARM REGISTERS

Registers C and D contain the time for the Watchdog Alarm. The two registers contain a time count from to 99.99 seconds in BCD. The value written into the Watchdog Alarm Registers can be written or read in any order. Any access to Registers C or D will cause the Watchdog Alarm to reinitialize and clears the Watchdog Flag bit and the Watchdog Interrupt Output. When a new value is entered or the Watchdog Registers are read, the Watchdog Timer will start counting down from the entered value to 0. When 0 is reached, the Watchdog Interrupt Output will go to the active state. The Watchdog Timer countdown is interrupted and reinitialized back to the entered value every time either of the registers is accessed. In this manner, controlled periodic accesses to the Watchdog Timer can prevent the Watchdog Alarm from ever going to an active level. If access does not occur, countdown alarm will be repetitive. The Watchdog Alarm registers always read the entered value. The actual countdown register is internal and is not readable. Writing Registers C and D to 0 will disable the Watchdog Alarm feature.

## COMMAND REGISTER

Address location 0B is the Command Register where mask bits, control bits, and flag bits reside. Bit 0 is the Time of Day Alarm Flag (TDF). When this bit is set internally to a logic 1, an alarm has occurred. The time of the alarm can be determined by reading the Time of Day Alarm registers. However, if the transfer enable bit is set to logic 0 the Time of Day registers may not reflect the exact time that the alarm occurred. This bit is read only and writing this register has no effect on the bit. The bit is reset when any of the Time of Day Alarm registers are read. Bit 1 is the Watchdog Alarm Flag (WAF). When this bit is set internally to a logic 1, a Watchdog Alarm has occurred. This bit is read only and writing this register has no effect on the bit. The bit is reset when any of the Watchdog Alarm registers are accessed. Bit 2 of the Command Register contains the Time of Day Alarm Mask Bit (TDM). When this bit is written to a logic 1, the Time of Day Alarm Interrupt Output is deactivated regardless of the value of the Time of Day Alarm Flag. When TDM is set to logic 0, the Time of Day Interrupt Output will go to the active state, which is determined by bits 0, 4, 5, and 6 of the Command Register. Bit 3 of the Command Register contains the Watchdog Alarm Mask bit (WAM). When this bit is written to a logic 1, the Watchdog Interrupt Output is deactivated regardless of the value in the Watchdog Alarm registers. When WAM is set to logic 0, the Watchdog Interrupt Output will go to the active state which is determined by bits 1, 4, 5, and 6 of the Command Register. These 4 bits define how Interrupt Output Pins  $\overline{\text{INTA}}$  and  $\overline{\text{INTB}}$  (INTB) will be operated. Bit 4 of the Command Register determines whether both interrupts will output a pulse or level when activated. If bit 4 is set to logic 1, the pulse mode is selected and  $\overline{\text{INTA}}$  will sink current for a minimum of 3 ms and then release. Output  $\overline{\text{INTB}}$  (INTB) will either sink or source current for a minimum of 3 ms depending on the level of bit 5. When bit 5 is set to logic 1, the B interrupt will source current. When bit 5 is set to logic 0, the B interrupt will sink current. Bit 6 of the Command Register directs which type of interrupt will be present on interrupt pins  $\overline{\text{INTA}}$  or  $\overline{\text{INTB}}$  (INTB). When set to logic 1,  $\overline{\text{INTA}}$  becomes the Time of Day Alarm Interrupt pin and  $\overline{\text{INTB}}$  (INTB) becomes the Watchdog Interrupt pin. When bit 6 is set to logic 0, the interrupt functions are reversed such that the Time of Day Alarm will be output on  $\overline{\text{INTB}}$  (INTB) and the Watchdog Interrupt will be output on  $\overline{\text{INTA}}$ . Caution should be exercised when dynamically setting this bit as the interrupts will be reversed even if in an active state. Bit 7 of the Command Register is for Transfer Enable (TE). The function of this bit is described in the Time of Day registers.

**TIME OF DAY ALARM MASK BITS** Figure 3

REGISTER			
(3)MINUTES	(5)HOURS	(7)DAYS	
1	1	1	ALARM ONCE PER MINUTE
0	1	1	ALARM WHEN MINUTES MATCH
0	0	1	ALARM WHEN HOURS AND MINUTES MATCH
0	0	0	ALARM WHEN HOURS, MINUTES, AND DAYS MATCH

**ABSOLUTE MAXIMUM RATINGS\***

Voltage on Any Pin Relative to Ground	-0.3V to +7.0V
Operating Temperature	0°C to 70°C
Storage Temperature	-40°C to +70°C
Soldering Temperature	260°C for 10 seconds (See Note 14)

\* This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operation sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods of time may affect reliability.

**RECOMMENDED DC OPERATING CONDITIONS** (0°C to 70°C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	NOTES
Power Supply Voltage	$V_{CC}$	4.5	5.0	5.5	V	10
Input Logic 1	$V_{IH}$	2.2		$V_{CC}+0.3$	V	10
Input Logic 0	$V_{IL}$	-0.3		0.8	V	10

**DC ELECTRICAL CHARACTERISTICS** (0°C to 70°C;  $V_{CC} = 5V \pm 10\%$ )



PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	NOTES
Input Leakage Current	$I_{IL}$	-1.0		+1.0	$\mu A$	
Output Leakage Current	$I_{LO}$	-1.0		+1.0	$\mu A$	
I/O Leakage Current $\overline{CE} \geq V_{IH} \leq V_{CC}$	$I_{LIO}$	-1.0		+1.0	$\mu A$	
Output Current @ 2.4V	$I_{OH}$	-1.0			mA	
Output Current @ 0.4V	$I_{OL}$	2.0			mA	13
Standby Current $\overline{CE} = 2.2V$	$I_{CCS1}$		3.0	7.0	mA	
Standby Current $\overline{CE} > V_{CC}-0.5$	$I_{CCS2}$			4.0	mA	
Active Current	$I_{CC}$			15	mA	
Write Protection Voltage	$V_{TP}$		4.25		V	




**CAPACITANCE** ( $t_A = 25^\circ C$ )

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	NOTES
Input Capacitance	$C_{IN}$		7	10	pF	
Output Capacitance	$C_{OUT}$		7	10	pF	
Input/Output Capacitance	$C_{IO}$		7	10	pF	

**AC ELECTRICAL CHARACTERISTICS** (0°C to 70°C;  $V_{CC} = 4.5V$  to 5.5V)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	NOTES
Read Cycle Time	$t_{RC}$	150			ns	1
Address Access Time	$t_{ACC}$			150	ns	
$\overline{CE}$ Access Time	$t_{CO}$			150	ns	
$\overline{OE}$ Access Time	$t_{OE}$			60	ns	
$\overline{OE}$ or $\overline{CE}$ to Output Active	$t_{COE}$	10			ns	
Output High Z from Deselect	$t_{OD}$			60	ns	
Output Hold from Address Change	$t_{OH}$	10			ns	
Write Cycle Time	$t_{WC}$	150			ns	
Write Pulse Width	$t_{WP}$	140			ns	3
Address Setup Time	$t_{AW}$	0			ns	
Write Recovery Time	$t_{WR}$	10			ns	
Output High Z from $\overline{WE}$	$t_{ODW}$			50	ns	
Output Active from $\overline{WE}$	$t_{OEWE}$	10			ns	
Data Setup Time	$t_{DS}$	45			ns	4
Data Hold Time	$t_{DH}$	0			ns	4,5
$\overline{INTA}$ , $\overline{INTB}$ Pulse Width	$t_{PW}$	3			ns	11,12

**READ CYCLE (NOTE 1)****WRITE CYCLE 1 (Notes 2, 6, 7)**

**WRITE CYCLE 2 (Notes 2, 8)****TIMING DIAGRAM: INTERRUPT  
OUTPUTS PULSE MODE (SEE NOTES 11, 12)****POWER-DOWN/POWER-UP CONDITION****POWER-UP/POWER-DOWN CONDITION**

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	NOTES
CE at V <sub>HH</sub> before Power-Down	t <sub>PD</sub>	0			μs	
V <sub>CC</sub> slew from 4.5V to 0V (CE at V <sub>HH</sub> )	t <sub>F</sub>	350			μs	
V <sub>CC</sub> slew from 0V to 4.5V (CE at V <sub>HH</sub> )	t <sub>R</sub>	100			μs	
CE at V <sub>HH</sub> after Power Up	t <sub>REC</sub>			150	ns	

(t<sub>A</sub>=25°C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	NOTES
Expected Data Retention Time	t <sub>DR</sub>	10			years	9

**WARNING:**

Under no circumstances are negative undershoots, of any amplitude, allowed when device is in battery backup mode.

**NOTES:**

1.  $\overline{WE}$  is high for a read cycle.
2.  $OE = V_{IH}$  or  $V_{IL}$ . If  $OE = V_{IH}$  during write cycle, the output buffers remain in a high impedance state.
3.  $t_{WP}$  is specified as the logical AND of the  $\overline{CE}$  and  $\overline{WE}$ .  $t_{WP}$  is measured from the latter of  $\overline{CE}$  or  $\overline{WE}$  going low to the earlier of  $\overline{CE}$  or  $\overline{WE}$  going high.
4.  $t_{DS}$  or  $t_{DH}$  are measured from the earlier of  $\overline{CE}$  or  $\overline{WE}$  going high.
5.  $t_{DH}$  is measured from  $\overline{WE}$  going high. If  $\overline{CE}$  is used to terminate the write cycle, then  $t_{DH} = 20$  ns.
6. If the  $\overline{CE}$  low transition occurs simultaneously with or later than the  $\overline{WE}$  low transition in Write Cycle 1, the output buffers remain in a high impedance state during this period.
7. If the  $\overline{CE}$  high transition occurs prior to or simultaneously with the  $\overline{WE}$  high transition, the output buffers remain in a high impedance state during this period.
8. If  $\overline{WE}$  is low or the  $\overline{WE}$  low transition occurs prior to or simultaneously with the  $\overline{CE}$  low transition, the output buffers remain in a high impedance state during this period.
9. Each DS1286 is marked with a four-digit date code AABB. AA designates the year of manufacture. BB designates the week of manufacture. The expected  $t_{DR}$  is defined as starting at the date of manufacture.
10. All voltages are referenced to ground.
11. Applies to both interrupt pins when the alarms are set to pulse.
12. Interrupt output occurs within 100 ns on the alarm condition existing.
13. Both  $\overline{INTA}$  and  $\overline{INTB}$  (INTB) are open drain outputs.
14. Real-Time Clock Modules can be successfully processed through conventional wave-soldering techniques as long as temperature exposure to the lithium energy source contained within does not exceed +85°C. Post-solder cleaning with water washing techniques is acceptable, provided that ultrasonic vibration is not used.

**AC TEST CONDITIONS**

Output Load: 100 pF + 1TTL Gate



Input Pulse Levels: 0-3.0V

Timing Measurement Reference Levels

Input: 1.5V

Output: 1.5V

Input Pulse Rise and Fall Times: 5 ns.

**DS1286 WATCHDOG TIMEKEEPER**

PKG	28-PIN	
DIM	MIN	MAX
A IN.	1.520	1.540
MM	38.61	39.12
B IN.	0.695	0.720
MM	17.65	18.29
C IN.	0.350	0.375
MM	8.89	9.52
D IN.	0.100	0.130
MM	2.54	3.30
E IN.	0.015	0.030
MM	0.38	0.76
F IN.	0.110	0.140
MM	2.79	3.56
G IN.	0.090	0.110
MM	2.29	2.79
H IN.	0.590	0.630
MM	14.99	16.00
J IN.	0.008	0.012
MM	0.20	0.30
K IN.	0.015	0.021
MM	0.38	0.53

NOTE: PINS 2,3,21,24 AND 25 ARE MISSING BY DESIGN

## Appendix E: Motor Datasheet



4118



- NEMA Size 17 Mounting
- Cost Effective
- Custom Windings Available (No Additional Cost)

## ■ SPECIFICATIONS

BIPOLAR	Dimension "A" Max	Model #	Amps/ Phase	Torque oz-in	Torque N-m	Resistance Ohm/Phase	Inductance mH/Phase	Inertia oz-in <sup>2</sup>	Weight Lbs.	Number of Leads
BIPOLAR	1.35" 34.3 mm	41185-02	1.30	45.0	0.32	2.8	3.6	0.18	0.40	4
		41185-04S	0.67	45.0	0.32	9.9	12.5	0.18	0.40	4
		41185-04F	1.31	45.0	0.32	2.5	3.1	0.18	0.40	4
		41185-09	0.90	45.0	0.28	5.3	6.7	0.18	0.40	4
		4118M-01	1.70	63.0	0.44	1.5	3.0	0.28	0.60	4
	1.57" 39.9 mm	4118M-06S	0.70	63.0	0.44	10.8	21.8	0.28	0.60	4
		4118M-06F	1.40	63.0	0.44	2.7	5.5	0.28	0.60	4
		4118L-01	2.00	83.0	0.59	1.4	2.7	0.37	0.70	4
	1.9" 48.3 mm	4118L-07S	1.05	83.0	0.59	5.2	9.4	0.37	0.70	4
		4118L-07F	2.10	83.0	0.59	1.3	2.3	0.37	0.70	4

UNIPOLAR	Dimension "A" Max	Model #	Amplifier Phase	Torque oz-in	Torque l-in	Resistance Ohm/Phase	Inductance mH/Phase	Inertia oz-in	Weight Lbs.	Number of Leads
	1.39" 34.3 mm	4118S-04	0.95	30.0	1.17	5.0	3.1	0.08	0.40	6
	1.57" 39.9 mm	4118M-06	1.00	45.0	0.35	5.4	5.5	0.28	0.60	6
	1.90" 48.3 mm	4118L-07	1.50	65.0	0.43	2.6	2.3	0.37	0.70	6
		4118L-25	0.45	65.0	0.35	25.0	17.4	0.37	0.70	6

\* Please complete our application data sheet for different windings


\* Power supply voltage can be any value as long as the driver output current is controlled at the rated current

\* Call Lin Engineering for additional bipolar torque curves.

\* Performance, use, and appearance specifications of the products listed here are subject to change without notice.

\* For operating temperatures, see page S4.








■ **DIMENSIONS** (inches)



## DID YOU KNOW...

The average lead time for prototypes is 3-7 business days. This includes custom windings and most shaft modifications.

### TORQUE CURVES





## Appendix F: 24V Power Supply Datasheet

### Input Specifications

Input Voltage Range	85-264 VAC
Input Current :	3.15 A/ 115 VAC 1.5A /230V
Frequency Range:	Range:47-63 Hz
Inrush Current, typ:	Cold Start 30A/115 VAC
Leakage Current	<=1mA/ 240 VAC

### Output Specifications

Voltage and Current	See Selection Chart
Load Regulation (0%-FL)	+/- 0.5 %
Line Regulation	+/- 0.5%
Voltage Tolerance	+/- 1-0%
Voltage Adjustment Range	2.16 ~ 26.4V
Ripple/ Noise (max)	150mVp-p
Over Voltage Protection	Shutdown; Re-power on
Overload Protection	105 ~ 150%, Constant 1 Limit Auto Recovery
Setup/ Rise/ Holdup (230 VAC)	1s, 30ms at full load

### General Specifications

Input-Out Isolation	I/P-O/P: 300 VAC I/P-G: 1500 VAC O/P: 0.5KVAC
Isolation Resistance	
I/P-O/P, I/P-G O/P-G:	500VDC/100 Ohm
Efficiency (3.3 V through 48V)	83% typ
Switching Frequency	135 KHz, (fixed, typical)
Safety	
EN60950	TUV File#9758434
UL1950	UL# E183223

### Environmental Specifications

Oper. Temperature	-10 ~ +60°C
Storage Temperature	-20 to +85°C
Relative Humidity	10% to 95%, non-cond *
Vibration	10 ~ 500Hz, 2G 10min./ 1cycle, Period for 60 min. Each Axes
EMC	CISPR22 (EN55022)B, EN61000-4-2,3,5,6,8,11 ENV50204
MTBF	EN61000-3-2,-3 314,900 Hrs

### Physical Specifications

Size	3.0" x 8.7" x 1.6"
Construction	Closed Frame
Weight	Weight 19.4 oz, (550g)